

# Toward sustainability in designing agricultural supply chain network: A case study on palm date

Abdolreza Hamdi-Asl<sup>a</sup>, Hossein Amoozad-Khalili<sup>b,\*</sup>, Reza Tavakkoli-Moghaddam<sup>c</sup>, Mostafa Hajiaghayi-Keshteli<sup>d</sup>

<sup>a</sup> Department of Industrial Engineering, Tehran Central Branch, Islamic Azad University, Tehran, Iran

<sup>b</sup> Department of Industrial Engineering, Nowshahr Branch, Islamic Azad University, Nowshahr, Iran

<sup>c</sup> School of Industrial Engineering, College of Engineering, University of Tehran, Tehran, Iran

<sup>d</sup> Tecnológico de Monterrey, Escuela de Ingeniería y Ciencias, Puebla, Mexico

**Abstract.** Nowadays, the agricultural and food supply chains have attracted both academia and industrial practitioners. This paper first considers the characteristics of the date product as one of the most well-known and rich fruits to design and address its supply chain design. Special characteristics in date products have made the supply chain design to be unique. Therefore, considering different customers along with the specific product flow is another contribution of this paper. Reportedly, there is no work on this topic. Several old and recent meta-heuristic algorithms are utilized in multi-objective meta-heuristics to reach better intensification and diversification trade-offs. By the Taguchi design experiment method, appropriate parameter values of the proposed algorithms are chosen. Besides, the solution quality is investigated by approaches including the relative percentage deviation (RPD), CPU time, and weighted LP-metric method. The results showed that a multi-objective Keshtel algorithm (MOKA) is more efficient and consistently outperforms other utilized algorithms.

**KEYWORDS:** Supply chain design; Agricultural supply chain; Sustainability; Date; Logistics.

## 1. Introduction and literature review

Recent developments in the supply chain network design (SCND) have led many companies and their users in public and private sectors to implement its settings in their industries to achieve the most added values out of a specific type of product. While many of them utilized the SCND to address their company's mission and vision, others tried to consider designing networks according to reducing costs, considering sustainability aspects, covering the ignored parts of different products, servicing customers, and enhancing the overall efficiency chains [1]. In this regard, companies avert their attention toward sustainable design. Agricultural products are among the most important products in production for society and addressing the potential market demand. However, far less attention has been devoted to designing an effective network for such products.

Previous studies only suggest minor contributions for these types of products, and hence the utilized supply chain networks often failed to introduce an efficient network for them. In addition, considering sustainability is mainly ignored, and therefore the proposed supply chain network could not find its optimized efficiency. van Berlo [2] presented a supply chain operations of vegetable processing. Their model incorporates farmer decisions to reduce supply chain costs and lacks location decisions. Jolayemi [3] considered a specific planting period and location of agricultural products to maximize profit. The model selects the most profitable product among a large number of products. In addition, the author tried to determine the amount of increase or decrease in profit from co-cultivation of any number of crops compared to their cultivation.

---

\* Corresponding author. Tel.: +989125988723

E-mail addresses: reza.hamdi758@gmail.com (A. Hamidi-Asl); amoozad92@yahoo.com (H. Amoozad-Khalili); tavakoli@ut.ac.ir (R. Tavakkoli-Moghaddam); mostafahaji@tec.mx (M. Hajiaghayi-Keshteli).

Allen and Schuster [4] reduced the amount of waste in agricultural production and focused on harvesting and storage capacities. Rantala [5] developed a model for seedlings and transportation and considered capacity constraints and product perishability, in addition to minimizing the costs and meeting customer demands. Designing a pea-based protein food SC network was considered by Apaiah and Hendrix [6]. The authors presented a supply chain model to reduce the costs considering chain equilibrium constraints, the capacity of each plant, and the different modes of transport.

Ferrer et al. [7] proposed a model for harvesting, transporting, and packaging crops. Manzini and Gebennini [8] designed a real-world model by adding time delay constraints at different distribution stages. In addition, by adding these constraints. Ahumada and Villalobos [9] and Ahumada et al. [10] planned to grow tomatoes and red peppers in the state of Sinaloa (northeastern Mexico) on farms with different locations, with employment constraints, holding and harvesting criteria, as well as water consumption. The proposed model evaluates these factors in two definite and uncertain conditions. Navazi et al. [11] designed a closed-loop supply chain for perishable products concerning recycling level in the reverse flow. The results of the problem showed enhancement in the environmental effect of waste reduction. Hajikhani et al. [12] designed a new plan to select the best supplier within a real agricultural case study. Using multi-objective functions, the results of using multiple metaheuristic algorithms revealed that the proposed algorithm applies to real-world problems. Kazemi et al. [13] designed an agricultural supply chain for rice products. Two objectives are presented to reduce total costs and also reduce soil erosion. Considering various scenarios, the results of the study showed improvements to the considered objectives.

Ahumada and Villalobos [14] worked quality and price of products based on the value of products, labor costs, and transportation modes. They developed an MIP model in a limited time (several weeks). The most important feature of their problem is to consider several farms in specific places. In this model, the quality of the product decreases during the shipping and delay stages. This model aims to maximize the farmer's income according to the quality of the products. In their model, the type and time range of cultivation is specified. Rong et al. [15] provided an optimization model about perishable products and focused mainly on maintaining the quality of products. In this model, the quality of agricultural products is reduced according to the temperature and storage time at each stage and product transfer conditions. This paper is to minimize overall SC costs while maintaining acceptable product quality. Teimoury et al. [16] considered the same chain in this area and probed the effect of supply, demand, and price.

Few studies have been conducted to address the reverse logistics issues of fresh fruits. Ahumada and Villalobos [17] worked on the perishability of agricultural products and vegetables as one of the first studies. Later, a mathematical model was presented for the same chain by Soto-Silva et al. [18] to optimize fruit freshness. A transportation planning model was provided to set some storage in the non-harvest season by Nadal-Roig and Plà-Aragónés [19]. Etemadnia et al. [20] also found the optimal locations of the wholesale facilities for the same chain.

Several works in this area have focused on multi-objective optimization approaches, aiming to make a trade-off between several conflicting goals [21]. For instance, Sarker and Ray [22] utilized the Epsilon-constraint and multi-objective optimization algorithms to address their multi-objective optimization model. Besides, most of the papers in this area mainly focused on price and demand. Paksoy et al. [23] minimized carbon dioxide emissions in forward logistics and supply chain costs in reverse logistics.

Recently, such concepts have been replaced by sustainability in this supply chain. Dehghanian and Mansour [24] measured responsibilities to examine social effects and the profit objective function to examine economic effects.

Recently, waste recovery and management were among the main suppositions in this area [25]. By considering reverse logistics, we consider all activities from the end to the beginning of a chain to re-use and reproduce that product or its variations [26]. Using reverse logistics can have more and better

competitive advantages [27]. Also, a few works consider waste to design closed-loop chains in the literature [28].

Banasik et al. [29] firstly considered industrial mushrooms and developed a closed-loop supply chain (CLSC) by the MILP, considering the economic and environmental aspects. Cheraghali et al. [30] considered citrus in their CLSC to minimize costs and maximize customer demand in both flows.

Supply chain responsiveness is also one of the key factors in such chains [31]. By growing population, day to day, researchers and the corresponding organizations know the importance of designing such chains in an optimized fashion better. According to Food and Agriculture Organization (FAO) in 2020, about 30 percent of global food production would be wasted. Consequently, the production resources waste, such as fuels, water, fertilizers matter, and cause negative effects [32]. In a nutshell, environmental aspects, strict regulations on waste, reverse logistics, and CLSC design are the major concerns in designing supply chain networks in this area. However, the only limited study addressed such issues for fruit and agricultural products. Jabarzadeh et al. [33] utilized concepts of reverse logistics for fruit supply chains. In their model, they minimized both costs and carbon dioxide emissions. Recently, Salehi-Amiri et al. [34] designed a CLSC network to minimize the total flow cost in both directions. They firstly considered walnut characteristics to model their network. Chouhan et al. [35] designed a multi-echelon sugarcane CLSC network. They addressed the model by recent metaheuristic algorithms.

One of the main products using its fruit and sub-products with high value in the nutrition pyramid is the date [36]. Date palm tree includes various sub-products, including date honey and date pedicles. In addition, various markets can use the date for their direct and indirect use [37]. In its direct use, the date is usually sent to the packaging center and then for general markets, which most of this product usage [38]. Indirect usage includes the processing date, seedling, pedicles, leaves, etc., to use in other markets such as the medical sector, animal food, etc. [39]. However, considering these settings for date palm trees as by-products has not been conducted before. Therefore, the remainder of this valuable product that can be re-used in the reverse flow is usually ignored. Considering the sustainability of the date palm tree can significantly increase its added value. Figure 1 shows the stance date among all dried fruit production worldwide.

{ Please insert Figure 1 about here. }

Therefore, in this study, the application of sustainable logistics for date products is taken into account. In this chain, the date and its sub-products are sent to various markets. Date products would send to different markets in the forward flow. Also, an environmental factor of such a program is taken into account. Two objective functions of costs and air pollution are applied for simultaneous economic and environmental consideration of the problem. A set of new multi-objective metaheuristic algorithms are utilized in this work.

As a result, the following are our primary goals and contributions in the literature:

- Reportedly, no same work exists on the issue above in this area, using palm date to design a sustainable network,
- In addition, the current study created unique mathematical modeling based on its characteristics, while the majority of prior studies indicated similar logistic networks,
- Due to its unique network, this study provides a new MILP model from a mathematical standpoint,
- To address the model, a new metaheuristic and hybrid technique are used.

The following sections are sorted as explained below. Section 2 entails the problem definition and shows the structure of the proposed SCND for the date industry. Section 3 details the solution approach,

including the Taguchi method, various proposed multi-objective metaheuristic algorithms, and exemplified parameter tuning. The results and their analyses are explained in Section 4, and Section 5 entails the conclusions and managerial insight.

## 2. Problem definition

This study is an optimization modeling for a forward date supply chain network, which embraces date palms, collection and distribution centers (DCs), date factories, customers, and by-product factories. As shown in Figure 2, the date product is collected from farmlands in the first level of the network. In the proposed network, the single-period chain is assumed. So, date product flow to collection and DC continues. After that, a percentage of products ships to date factories and market. Lastly, Waste date products are also gathered and transported to by-product factories.

{ Please insert Figure 2 about here. }

### 2.1. Proposed model

Here, we aim to develop our model based on the assumptions mentioned above. The notations of the presented model are shown in Table 1.

{ Please insert Table 1 about here. }

The details of the MILP model are as follows:

$$\begin{aligned} \text{Min } Z_1 = & \sum_{i=1}^I f_i U_i + \sum_{k=1}^K f_k W_k + \sum_{m=1}^M f_m B_m + \sum_{i=1}^I \sum_{j=1}^J C_{ij} X_{ij} + \sum_{j=1}^J \sum_{k=1}^K C_{jk} G_{jk} + \sum_{k=1}^K \sum_{l=1}^L C_{kl} S_{kl} \\ & + \sum_{k=1}^K \sum_{m=1}^M C_{km} E_{km} + \sum_{i=1}^I \sum_{n=1}^N C_{in} R_{in} \end{aligned} \quad (1)$$

$$\text{Min } Z_2 = \left( \sum_{i=1}^I U_i + \sum_{k=1}^K f_k + \sum_{m=1}^M f_m \right) \times EM \quad (2)$$

s.t.

$$(1-v_i) \times \xi_i \times U_i = \sum_{j=1}^J X_{ij} \quad \forall i \in I \quad (3)$$

$$\sum_{j=1}^J Y_j \geq 1 \quad (4)$$

$$\sum_{i=1}^I X_{ij} \leq \xi_j \quad \forall j \in J \quad (5)$$

$$\sum_{k=1}^K G_{jk} \leq \sum_{i=1}^I X_{ij} \quad \forall j \in J \quad (6)$$

$$\sum_{k=1}^K W_k \geq 1 \quad (7)$$

$$\sum_{j=1}^I G_{jk} \leq \xi_k \times w_k \quad \forall k \in K \quad (8)$$

$$\sum_{k=1}^K S_{kl}^t = D_l \quad \forall l \in L \quad (9)$$

$$\sum_{m=1}^M B_m \geq 1 \quad (10)$$

$$\sum_{i=1}^I R_{im} + \sum_{k=1}^K E_{km} \leq \xi_m \times B_m \quad \forall m \in M \quad (11)$$

$$\sum_{i=1}^I R_{im} \leq \xi_i \times v_i \quad \forall m \in M \quad (12)$$

$$\sum_{k=1}^K E_{km} = \xi_m \times \rho_k \quad \forall m \in M \quad (13)$$

$$U_i, W_k, B_m \in \{0,1\} \quad \forall i \in I, \forall k \in K, \forall m \in M \quad (14)$$

$$X_{ij}, G_{jk}, S_{kl}, E_{km}, R_{im} \geq 0 \quad \forall i \in I, \forall j \in J, \forall k \in K, \forall l \in L, \forall m \in M \quad (15)$$

According to the objective function (1), the objective function for the date supply chain network is provided. Objective function (2) minimizes total CO<sub>2</sub> emission using opened facilities. In Constraint (3), the production capacity of each farmland must be equal to or greater than the number of products shipped from date farmlands to collection and DCs. Here, waste products are excluding from the shipped products to collection and DCs. In Constraint (4), we ensure that at least one DC and collection should be opened. Constraint (5) assures the capacity of DCs if it is opened should be equal to or greater than the quantity of date products transported from farmlands to collection and DCs. We imply that the quantity of products transported from date farmlands to collection and DCs should be equal or greater than the quantity of products transported from collection and DCs to date factories in Constraint (6). Constraint (7) ensures that at least one date factory should be opened. If it is opened, the capacity of factories should be equal to or greater than the quantity of products transported from collection and DCs to date factories in Constraint (8). Constraint (9) indicates that the quantity of products transported from date factories to customers should be equal to customers' demand. Constraint (10) determines that at least one by-product factory should be opened. We indicate that the capacity of dye factories if it is open, should be equal to or greater than the quantity of waste products transported from farmland and date factories to dye in Constraint (11). The quantity of waste shipped from date farmlands to dye factories should be equal to or greater than the waste products of farmlands in Constraint (12). Constraint (13) shows that waste production of farmlands should be equal to or greater than the quantity of waste products shipped from date factories to dye factories. Constraint (14) represents the binary variables. Constraints (15) enforces the positivity of the decision variables.

## 2.2. Applied stochastic programming

Stochastic programming is a prevalent method to address uncertainty in parameters and situations where the objective value function is deemed to carry out well on its average values. This method is utilized in multi-tire programming [40, 41]. Therefore, basic linear methods cannot be applied when dealing with uncertain objective functions in this condition and to find the best answers. The uncertain situation when dealing with customers and uncertainty in their daily demand for date products made

problem to employ a stochastic approach. Utilizing this approach enables to conduct the problem in a real-world condition where daily demand is not certain. To apply this uncertainty chance constraint method is taken into account. Some previous works have considered the same approach to deal with their problems [42- 44]. According to the chance constraint approach,  $\bar{x}$  is regarded as a decision variable to include a possibilistic limit into the model [45]. The following equation shows how this method is applied for the considered modeling.

$$\Pr \left( \sum_{k=1}^K S_{kl}^t - D_l - \bar{x} \right) \geq \psi \quad (16)$$

Using the confidence level  $\psi$ , we have:

$$\bar{x} = \min \left\{ x \mid \Pr \left( \sum_{k=1}^K S_{kl}^t - D_l \leq \bar{x} \right) \geq \psi \right\} \quad (17)$$

The Eq. (17) can be converted into the following equation:

$$G = \sum_{k=1}^K S_{kl}^t - D_l - \bar{x} \quad (18)$$

Here we define  $\gamma_s$  as an uncertain parameter with the normal distribution. Hence,  $G$  also follows a normal distribution.

$$E(G) = \sum_{k=1}^K S_{kl}^t - D_l - \bar{x} \quad (19)$$

$$Var(G) = Var(\gamma_s) \left[ \sum_{k=1}^K S_{kl}^t - D_l \right]^2 \quad (20)$$

$E(G)$  is the expected value of  $G$ . Since  $G$  follows a normal distribution, the following equation follows a standard normal distribution:

$$\Pr \left( \frac{G - E(G)}{Var(G)} < -\frac{E(G)}{Var(G)} \right) > \psi \quad (21)$$

If we define  $\omega = \frac{G - E(G)}{\sqrt{Var(G)}}$ , then we have:

$$\Pr \left( \omega \leq \frac{E(G)}{\sqrt{Var(G)}} \right) > \psi \quad (22)$$

$$\varphi^{-1}(\psi) \leq -\frac{E(G)}{\sqrt{\text{Var}(G)}} \quad (23)$$

Here, we can write:

$$\varphi^{-1}(\psi)\sqrt{\text{Var}(G)} \leq -E(G) \quad (24)$$

$$\varphi^{-1}(\psi)\sqrt{\text{Var}(\gamma_s)} \left[ \sum_{k=1}^K S_{kl}^t - D_l \right] \leq \sum_{k=1}^K S_{kl}^t - D_l \times \mu_i + \bar{x} \quad (25)$$

### 2.3. Weighted LP-metric method

The LP-metric method, also known as the comprehensive benchmark method, is to solve multi-objective models. For a problem with  $n$  objective functions, the optimal value of each objective function (from the first to the  $n$ -th) must be calculated independently of the rest of the other  $n-1$  objective functions, taking into account all the constraints of the problem. Since the closer the objective functions are to their optimal values, the more desirable the answers to the problem, the problem looks for an objective function that uses all those functions to get closer to their optimal values. Therefore, we define the objective function as follows:

$$\text{Min } Z = \sum_{i=1}^k \left( \frac{f_i^* - f_i}{f_i^*} \right)^p \quad (26)$$

In Eq. (26), the values of  $f_i^*$  are equal to the optimal objective function values of the problem, and the values of  $f_i$  are the values related to each of the objective functions of the problem.

#### 2.3.1. Defining norm

In functional algebra and analysis, a norm means a vector or a continuous function that assigns a positive number called length or size to any vectors in a vector space. Different values are given for  $p$ , some of which are considered  $p=1$  and some  $p=2$ ; it is clear that the first case means that the relative sum of deviations is minimized, and the second case means minimizing the sum of the second power of relative deviations.

#### 2.3.2. LP-metric characteristic

This method minimizes the sum of the relative deviations of the objectives from their optimum value and combines multiple objective functions into a single objective [46]. The LP-metric method receives more attention for two reasons:

- It requires less information from the decision-makers.
- It is easy to use in practice.

The measure of the proximity of a solution is as follows, so for minimizing  $Z$ , we have:

$$\text{Min } Z = \sum_{i=1}^k W_i \left( \frac{Z_i^* - Z_i}{Z_i^*} \right)^p \quad (27)$$

Eq. (27) is the same as Eq. (26). The difference is that the weight values of  $W_i$  have been added to it. These weight values will help the objective function to achieve the optimal state more quickly. On the other hand, with the finding of the optimal level in the LP-metric method, this weight vector function will advance the answer to the optimization more quickly. Also, the following equation for the sum of  $W_i$  is considered:

$$\sum_{i=1}^k W_i = 1 \quad (28)$$

To eliminate the problem of differences in the scales of the objectives, the deviation of the ideal answer of the  $i$ -th objective will be divided by  $Z_i^*$ . It also determines the degree of emphasis on deviations so that the larger the value, the greater the emphasis on the largest deviation [47]. The overall objective function of the LP-metric method must also be minimized to minimize deviations from the ideal.

In this method, we optimize the objective functions separately through optimization software, considering all the limitations of the problem, and consider the optimal solutions obtained from each objective function as  $Z_i^*$ . Now, we will try to minimize the deviation function resulting from the above two functions. Therefore, the LP-metric method is defined as follows:

$$\text{Min } Z = \sum_{i=1}^k W_i \left( \frac{Z_i^* - Z_i}{Z_i^*} \right)^p \quad (29)$$

s.t.

$$g_i (X_1, X_2, \dots, X_n) \leq b_i \quad (30)$$

$$Z_i = f_i (X_1, X_2, \dots, X_n) \quad (31)$$

$$X_i \geq 0 \quad i=1, 2, \dots, k \quad (32)$$

$$\forall Z_i \quad (33)$$

Using the first norm, the proposed modeling can be changed by:

$$\begin{aligned} \text{Min } Z = & \\ & w_1 \frac{Z_1^* \left( \sum_{i=1}^I f_i U_i + \sum_{k=1}^K f_k W_k + \sum_{m=1}^M f_m B_m + \sum_{i=1}^I \sum_{j=1}^J C_{ij} X_{ij} + \sum_{j=1}^J \sum_{k=1}^K C_{jk} G_{jk} + \sum_{k=1}^K \sum_{l=1}^L C_{kl} S_{kl} + \sum_{k=1}^K \sum_{m=1}^M C_{km} E_{km} + \sum_{i=1}^I \sum_{n=1}^N C_{in} R_{in} \right)}{Z_1^*} \\ & + w_2 \frac{Z_2^* \left( \left( \sum_{i=1}^I U_i + \sum_{k=1}^K f_k + \sum_{m=1}^M f_m \right) \times EM \right)}{Z_2^*} \end{aligned} \quad (34)$$

Using Eq. (34) as an objective function and Eq. (27) in the constraints, the problem can be solved with different Pareto solutions to find the optimum answer.



### 3. Solution approach

This study formulates a bi-objective programming model, which considers the total costs of the proposed SCND for date product and CO<sub>2</sub> emission. This model uses several binary variables for opening different centers, which ultimately leads to the complexity of the proposed model. Generally, the problem size is directly associated with the problem complexity as a larger-sized problem yields more complexity [48, 49]. In addition, exact approaches to find optimal solutions can always be time-consuming in these problems [50]. So, in this section, we explained the implemented strategy for the encoding/decoding plan for the suggested meta-heuristics.

#### 3.1. Encode/decode plan

Strategies such as using the matrix of Michalewicz by Michalewicz et al. [51], Prüfer numbers by Prüfer [52], and priority-based solution method by Gen et al. [53] represent multiple approaches to encode the problem solutions. The proposed method by Gen et al. [53] (priority-based solution method) is utilized in this work. The schematic plan to encode and decode the purpose for chromosomes is shown in Figure 3. Each section has three rows in which the first one shows the flow among the defined centers in the problem. The other two rows are the developed random number between [0] and 1, and the last one represents the priority decode plan.

{ Please insert Figure 3 about here. }

#### 3.2. Multi-objective Keshtel algorithm (MOKA)

The KA, developed by Hajiaghaei-Keshteli and Aminnayeri [54], is based on observation and applying the unusual behavior of Keshtel ducks when feeding.

Considering these amazing characterizes, the MOKA [30] considers simultaneous objectives and optimizes them. The prosperity of this solution method is that it also guarantees the problem's feasibility [55]. The overview of this solution method is depicted in Figure 4.

{ Please insert Figure 4 about here. }

#### 3.3. Multi-objective simulated annealing (MOSA)

The SA algorithm, proposed by Kirkpatrick et al. [56], is one of the famous single-solution algorithms in this regard [57]. Eq. (35) examines this procedure for this algorithm as follows [58]:

$$\begin{aligned} x &: \text{Initial solutions} \\ x' &: \text{Newly developed solutions} \\ \Delta f_j &= f_j(x') - f_j(x); \quad j = 1, 2, \dots, n \end{aligned} \tag{35}$$

Figure 5 shows the pseudocode of the proposed MOSA.

{ Please insert Figure 5 about here. }

#### 3.4. Implemented NSGA-II and NRGAs

This section considers the NRGAs and NSGA-II proposed by Al Jadaan et al. [59] and Deb et al. [60], respectively.

The selection mechanism is one of the different points when using NRGAs or NSGA-II, as the NRGAs and NSGA-II use the roulette wheel and binary tournament, respectively [61]. Figure 6 shows the pseudocode of these two algorithms.

{Please insert Figure 6 about here.}

## 4. Computational results

An intelligent experiment would be catered to investigate the efficiency of the utilized approaches, which are investigated at three levels. Random data are first created. The Taguchi approach and response surface methodology (RSM) are carried out [62, 63]. Finally, the results would be compared, and the best method is picked base on the defined norms [64].

### 4.1. Generating data

To investigate the productivity of the presented algorithms, three diverse problem sizes are proposed. Table 2 illustrates the problem sizes and their associated settings. The proposed meta-heuristic algorithms are investigated by the instances. These settings include the dimensions from small sizes to large-sized problems. In this regard, a set of farmlands ( $i$ ), collection and DCs ( $j$ ), date factories ( $k$ ), customers ( $l$ ), and by-product factories ( $m$ ) are considered. Also, Table 3 represents the considered parameters and their values to initialize the given problem.

{Please insert Table 2 about here.}

{Please insert Table 3 about here.}

### 4.2. Parameter setting

To get the most benefits out of the utilized metaheuristic algorithms, each associated parameter should be tuned. Tuning enables the metaheuristic algorithms to perform much better, and ultimately, they will get better output results. This enhancement in the algorithm's performance shows itself in both the quality of the solutions and the time to reach the optimum answer. The Taguchi method is employed to ascertain an appropriate value for the proposed algorithm's parameters. Table 4 shows the parameters and their levels.

The Taguchi experiment allows tuning the algorithm's parameters while reducing the number of tries to achieve them. Hence, when the objective function is minimization, the "smaller-is-better" concept is utilized to deal with the problem [65]. Also, Eq. (27) is represented to investigate the signal-to-noise ratio [66].

$$S / N = -10 \log \left( \frac{\sum_{i=1}^n Y_i^2}{n} \right) \quad (36)$$

where  $n$  determines the number of experiments while  $Y$  determines the observed data [67]. Ten test problems in three categories have been run 40 times to achieve the best levels of each algorithm. Since the problem cannot be solved and compared straight, the relative percentage deviation (RPD) is used. The RPD is showed as follows [68, 69]:

$$RPD = \frac{|Alg_{sol} - Min_{sol}|}{Min_{sol}} \quad (37)$$

where  $A_{lg_{sol}}$  represents the value of objective in individual trials, also,  $Min_{sol}$  shows the best solution among all trials [70]. Next, this value is changed into the RPD, and mean values are achieved. Then, the Taguchi method sets the orthogonal arrays to reduce the experiments for algorithms [71].  $L_9$  design opts for the MOKA,  $L_{16}$  design opts for MOSA, and  $L_{27}$  for NSGA-II and NREGA [72], respectively. Figs. 7-10 illustrates the signal-to-noise ratio for all the given meta-heuristic algorithms. The tuned algorithm's parameters are described in Table 5.

{Please insert Table 4 about here.}  
 {Please insert Figure 7 about here.}  
 {Please insert Figure 8 about here.}  
 {Please insert Figure 9 about here.}  
 {Please insert Figure 10 about here.}  
 {Please insert Table 5 about here.}

#### 4.3. Comparing algorithms and the utilized metrics

To consider the applicability and practicality of the two proposed meta-heuristics, this section represents two metrics that can evaluate different characteristics of the metaheuristics, including the mean ideal distance (MID) and CPU time [73, 74]. These metrics are described below:

- a) (MID): To evaluate this metric, the difference between Pareto solutions and ideal ones must be calculated [75]. This evaluation approach is described as Eq. (35) for two objectives function models [76].

$$MID = \frac{\sum_{i=1}^n \sqrt{\left( \frac{f_i^1 - f_{best}^1}{f_{1total}^{max} - f_{1total}^{min}} \right)^2 + \left( \frac{f_i^2 - f_{best}^2}{f_{2total}^{max} - f_{2total}^{min}} \right)^2}}{n} \quad (38)$$

$n$ : The number of non-dominated answers

$f_i^1, f_i^2$ : The value of the  $i^{th}$  non-dominated answers for the two objectives

The algorithm has better performance in fewer values of MID [77].

- b) (CPU): The less the computational time, the better the performance of the algorithm.

Here we categorized problems into three different sizes, such as small-sized problem (1-3), medium-sized problem (4-7), and large-sized problem (8-10). The problem answers are obtained using the computer device with 12GB RAM, 2.3GHz CPU, windows 10 OS. The results are shown in Table 6.

The analysis of variance (ANOVA) is conducted to compare these two metrics. The interval plots for the mentioned metrics are shown in Figures 11-12.

{Please insert Table 6 about here.}  
 {Please insert Figure 11 about here.}  
 {Please insert Figure 12 about here.}

As can be concluded from Figures 11 and 12, the MOKA has superiority in terms of the MID, and in terms of CPU time, the MOSA showed better performances. Comparing the results of CPU time indicates that MOSA is the best algorithm in all the problem samples, and it can reach its best results in a shorter time. In addition, it has the best variance. In terms of the quality of the problem outcomes, considering the MID is handy. The MOKA shows the best results since it has a minimum MID average. Also, the second-best algorithm in this regard is MOSA, with lower variance concerning the MOKA. The Pareto solutions of the problem outcome are described in Table 7 and Figure 13 for test problem 6.

{Please insert Table 7 about here.}  
{Please insert Figure 13 about here.}

#### **4.4. Sensitivity analysis**

Here, we do sensitivity analysis on the main parameters. [Table 8](#) has demonstrated the model conduct when changing in values of demand rate. Model changeability, the effects on various parameters, and the objective functions of each metaheuristic algorithm are considered. The more the demand, the more the total costs of the proposed network. In addition, other parameters affected by this change are illustrated in [Table 8](#).

Next, the transportation costs have been taken into account. Thus, we firstly enhanced and then declined its value by 20 and 40 percent. The changes in other parameters are shown in [Table 9](#). As aforementioned, it is interesting to note that increasing the value of opening and purchasing costs increases their value. However, the increase in purchasing costs is not much. In addition, such an increase would decrease the operation cost since a new center must be opened with a lower process cost.

{Please insert Table 8 about here.}  
{Please insert Table 9 about here.}

Last but not least, we consider the changes in the emission parameters. As stated in [Table 10](#), the more emission will have more decision variables and objective functions. This change indicates that it must be considered when opening new facilities. Hence, the majority of the opening costs are affected by the emission ratio. Therefore, other variables are dependent on this change.

{Please insert Table 10 about here.}

### **5. Conclusion and further perspective**

Considering the agricultural supply chain and determining optimal flow among the different levels of a product's value chain can significantly affect the profitability of certain products. An efficient network design is required to guarantee the maximum productivity for a specific agricultural product, such as date. Designing such a network for this important product decreases the total costs of the date industry and increases the efficiency of providing the customers with their potential needs. These products can be transferred to different markets while the emission is reduced. This consideration has failed in previous studies. Therefore, an efficient network is designed for date products to increase product flow efficiency in a forward direction and reduce the total associated costs of the supply chain by optimizing the costs and emissions. The utilized MILP model is designed to calculate the number of opened centers. In addition, this model minimizes the total logistic costs.

The study's finding revealed that considering by-product factories for waste collection can significantly affect the model outcome by reducing the total costs of the proposed supply chain network and reducing CO<sub>2</sub> emissions. In addition, the model is so responsive to transportation costs that increasing the logistics costs would increase opening costs. On the other hand, when the logistics costs are lower, there is less need to open new facilities since it is logical to open new facilities when logistic costs are lower. Increasing the demand rate would also increase the total costs of the date supply chain network since more demand means more transportation, opening, and procession costs. The emission rate also acts the same. To obtain expected results, managers can actively focus on various aspects of the date supply chain, such as opening and closing facilities, logistics costs, distributing their demands

in various periods, and concerning environmental factors. In addition, they can adjust some of these parameters to get the desired outcome.

From the managerial aspect, considering forward direction might result in problem optimality. However, taking particular sites to by-products would guarantee the most benefit out of the date product industry. Also, the conducted sensitivity analyses on the product showed an increase in the opening costs when increasing its value. Therefore, managers could wisely decide to justify or considers a unique trade-off between these two costs. Both governmental and private sectors are the beneficiaries of the prevalent works regarding cost, quality, and social and environmental aspects of this optimization. In fact, the key factors of competitive advantages in the supply chain would be optimized by optimizing the network. So, all stakeholders relevant to the supply chain can take advantage of the benefits of these optimizations. Even the customers of this chain can utilize the better quality and the lower cost of the product. Furthermore, last but not least, by enforcing and establishing green consideration, the environmental factor is also enhanced. Thus, this action itself can provide inestimable advantages, mostly in such social and environmental aspects.

Therefore, emerging topics, including incorporating the old and new metaheuristic algorithms, are highly recommended. To accomplish a detailed managerial decision, it is quite fundamental to enforce and analyze the settings of the proposed study on other case parameters. To move forward with this study, social and environmental factors, water consumption, and job employment opportunity should help the model development for simultaneous consideration of costs.

## Acknowledgments

The authors would like to thank the Editor-in-Chief, Section Editor of the "Scientia Itrania" journal, and autonomous reviewers for their helpful comments and suggestions, which significantly improved the presentation of this paper. Also, the support of the Iranian Operations Research Society is highly acknowledged by the third author, as the board member of this society.

## References

1. Hosseini, S.M., Paydar, M.M. and Hajiaghaei-Keshteli, M. "Recovery solutions for ecotourism centers during the Covid-19 pandemic: Utilizing Fuzzy DEMATEL and Fuzzy VIKOR methods", *Expert Systems with Applications*, **185**, p. 115594 (2021).
2. van Berlo, J.M. "A decision support tool for the vegetable processing industry; an integrative approach of market, industry and agriculture", *Agricultural Systems*, **43**(1), pp.91-109 (1993).
3. Jolayemi, J.K. "An integrated model for planning and managing multi-regional mixed-crop farming schemes", *Ecological modelling*, **84**(1-3), pp. 63-74 (1996).
4. Allen, S.J. and Schuster, E.W. "Controlling the risk for an agricultural harvest", *Manufacturing & Service Operations Management*, **6**(3), pp. 225-236 (2004).
5. Rantala, J. "Optimizing the supply chain strategy of a multi-unit Finnish nursery company", *Silva Fennica*, **38**(2), pp. 203–215 (2004).
6. Apaiah, R.K. and Hendrix, E.M. "Design of a supply chain network for pea-based novel protein foods", *Journal of Food Engineering*, **70**(3), pp. 383-391 (2005).
7. Ferrer, J.C., Mac Cawley, A., Maturana, S., Toloza, S. and Vera, J. "An optimization approach for scheduling wine grape harvest operations", *International Journal of Production Economics*, **112**(2), pp. 985-999 (2008).
8. Manzini, R. and Gebennini, E. "Optimization models for the dynamic facility location and allocation problem", *International Journal of Production Research*, **46**(8), pp. 2061-2086 (2008).

9. Ahumada, O. and Villalobos, J.R. "A tactical model for planning the production and distribution of fresh produce", *Annals of Operations Research*, **190**(1), pp. 339-358 (2011).
10. Ahumada, O., Villalobos, J.R. and Mason, A.N. "Tactical planning of the production and distribution of fresh agricultural products under uncertainty", *Agricultural Systems*, **112**, pp. 17-26 (2012).
11. Navazi, F., Sazvar, Z. and Tavakkoli-Moghaddam, R. "A sustainable closed-loop location-routing-inventory problem for perishable products", *Scientia Iranica*, Article in Press (2021).
12. Hajikhani, A., Khalilzadeh, M. and Sadjadi, S.J. "A fuzzy multi-objective multi-product supplier selection and order allocation problem in supply chain under coverage and price considerations: An urban agricultural case study", *Scientia Iranica*, **25**(1), pp. 431-449 (2018).
13. Kazemi, M.J., Paydar, M.M. and Safaei, A.S. "Designing a bi-objective rice supply chain considering environmental impacts under uncertainty", *Scientia Iranica*, Article in Press (2021).
14. Ahumada, O. and Villalobos, J.R. "Operational model for planning the harvest and distribution of perishable agricultural products", *International Journal of Production Economics*, **133**(2), pp. 677-687 (2011).
15. Rong, A., Akkerman, R. and Grunow, M. "An optimization approach for managing fresh food quality throughout the supply chain", *International Journal of Production Economics*, **131**(1), pp. 421-429 (2011).
16. Teimoury, E., Nedaei, H., Ansari, S. and Sabbaghi, M. "A multi-objective analysis for import quota policy making in a perishable fruit and vegetable supply chain: A system dynamics approach", *Computers and electronics in agriculture*, **93**, pp. 37-45 (2013).
17. Ahumada, O. and Villalobos, J.R. "Application of planning models in the agri-food supply chain: A review", *European journal of Operational Research*, **196**(1), pp. 1-20 (2009).
18. Soto-Silva, W.E., Nadal-Roig, E., González-Araya, M.C. and Pla-Aragones, L.M. "Operational research models applied to the fresh fruit supply chain", *European Journal of Operational Research*, **251**(2), pp. 345-355 (2016).
19. Nadal-Roig, E. and Plà-Aragonés, L.M. "Optimal transport planning for the supply to a fruit logistic centre", In: *Handbook of Operations Research in Agriculture and the Agri-Food Industry*, pp. 163-177, Springer, New York, NY (2015).
20. Etemadnia, H., Goetz, S.J., Canning, P. and Tavallali, M.S. "Optimal wholesale facilities location within the fruit and vegetables supply chain with bimodal transportation options: An LP-MIP heuristic approach", *European Journal of Operational Research*, **244**(2), pp. 648-661 (2015).
21. Madoumier, M., Trystram, G., Sébastien, P. and Collignan, A. "Towards a holistic approach for multi-objective optimization of food processes: a critical review", *Trends in Food Science & Technology*, **86**, pp. 1-15 (2019).
22. Sarker, R. and Ray, T. "An improved evolutionary algorithm for solving multi-objective crop planning models", *Computers and Electronics in Agriculture*, **68**(2), pp. 191-199 (2009).
23. Paksoy, T., Özceylan, E. and Weber, G.W. "A multi objective model for optimization of a green supply chain network", In: *AIP Conference Proceedings*, **1239**(1), pp. 311-320, American Institute of Physics (2010).
24. Dehghanian, F. and Mansour, S. "Designing sustainable recovery network of end-of-life products using genetic algorithm", *Resources, Conservation and Recycling*, **53**(10), pp. 559-570 (2009).
25. Jabarzadeh, Y., Reyhani Yamchi, H. and Ghaffarinasab, N. "A Multi-Objective Mathematical Model For Managing Sustainable Direct and Reverse Supply Chain of Apple Considering Foreign Markets", *Journal of International Business Administration*, **3**(1), pp. 139-166 (2020).
26. Fleischmann, M., Bloemhof-Ruwaard, J.M., Dekker, R., Van der Laan, E., Van Nunen, J.A. and Van Wassenhove, L.N. "Quantitative models for reverse logistics: A review", *European Journal of Operational Research*, **103**(1), pp. 1-17 (1997).

27. Stock, J.R. and Mulki, J.P. "Product returns processing: an examination of practices of manufacturers, wholesalers/distributors, and retailers", *Journal of Business Logistics*, **30**(1), pp. 33-62 (2009).
28. Zhang, Y., Chu, F., Che, A., Yu, Y. and Feng, X. "Novel model and kernel search heuristic for multi-period closed-loop food supply chain planning with returnable transport items", *International Journal of Production Research*, **57**(23), pp. 7439-7456 (2019).
29. Banasik, A., Kanellopoulos, A., Claassen, G.D.H., Bloemhof-Ruwaard, J.M. and van der Vorst, J.G. "Closing loops in agricultural supply chains using multi-objective optimization: A case study of an industrial mushroom supply chain", *International Journal of Production Economics*, **183**, pp. 409-420 (2017).
30. Cheraghalipour, A., Paydar, M.M. and Hajiaghahi-Keshteli, M. "A bi-objective optimization for citrus closed-loop supply chain using Pareto-based algorithms", *Applied Soft Computing*, **69**, pp. 33-59 (2018).
31. Azaron, A., Venkatadri, U. and Farhang Doost, A. "Designing profitable and responsive supply chains under uncertainty", *International Journal of Production Research*, **59**(1), pp. 213-225 (2021).
32. Göbel, C., Langen, N., Blumenthal, A., Teitscheid, P. and Ritter, G. "Cutting food waste through cooperation along the food supply chain", *Sustainability*, **7**(2), pp. 1429-1445 (2015).
33. Jabarzadeh, Y., Yamchi, H.R., Kumar, V. and Ghaffarinasab, N. "A multi-objective mixed-integer linear model for sustainable fruit closed-loop supply chain network", *Management of Environmental Quality: An International Journal*, **31**(5), pp. 1351-1373 (2020).
34. Salehi-Amiri, A., Zahedi, A., Akbapour, N. and Hajiaghahi-Keshteli, M. "Designing a sustainable closed-loop supply chain network for walnut industry", *Renewable and Sustainable Energy Reviews*, **141**, p. 110821 (2021).
35. Chouhan, V.K., Khan, S.H. and Hajiaghahi-Keshteli, M. "Metaheuristic approaches to design and address multi-echelon sugarcane closed-loop supply chain network", *Soft Computing*, **25**(16), pp. 11377-11404 (2021).
36. Peters, C.J., Fick, G.W. and Wilkins, J.L. "Cultivating better nutrition: can the food pyramid help translate dietary recommendations into agricultural goals?", *Agronomy Journal*, **95**(6), pp. 1424-1431 (2003).
37. Alotaibi, M.D., Alshammari, B.A., Saba, N., Alothman, O.Y., Sanjay, M.R., Almutairi, Z. and Jawaid, M. "Characterization of natural fiber obtained from different parts of date palm tree (*Phoenix dactylifera* L.)", *International Journal of Biological Macromolecules*, **135**, pp. 69-76 (2019).
38. Hanieh, A.A., Hasan, A. and Assi, M. "Date palm trees supply chain and sustainable model", *Journal of Cleaner Production*, **258**, p. 120951 (2020).
39. Alawar, A., Hamed, A.M. and Al-Kaabi, K. "Characterization of treated date palm tree fiber as composite reinforcement", *Composites Part B: Engineering*, **40**(7), pp. 601-606 (2009).
40. Schultz, R., Stougie, L. and Van Der Vlerk, M.H. "Two-stage stochastic integer programming: A survey", *Statistica Neerlandica*, **50**(3), pp. 404-416 (1996).
41. Shapiro, A. and Philpott, A. "A tutorial on stochastic programming", *Manuscript, Available at [www2.isye.gatech.edu/ashapiro/publications.html](http://www2.isye.gatech.edu/ashapiro/publications.html)*, 17 (2007).
42. Shah, P.J., Anagnostopoulos, T., Zaslavsky, A. and Behdad, S. "A stochastic optimization framework for planning of waste collection and value recovery operations in smart and sustainable cities", *Waste management*, **78**, pp. 104-114 (2018).
43. Zahiri, B., Torabi, S.A., Mohammadi, M. and Aghabegloo, M. "A multi-stage stochastic programming approach for blood supply chain planning", *Computers & Industrial Engineering*, **122**, pp. 1-14 (2018).


44. Zhou, Z., Zhang, J., Liu, P., Li, Z., Georgiadis, M.C. and Pistikopoulos, E.N. "A two-stage stochastic programming model for the optimal design of distributed energy systems", *Applied Energy*, **103**, pp. 135-144 (2013).
45. Heyman, D.P. and Sobel, M.J. "Stochastic models in operations research: stochastic optimization", Vol. 2, Courier Corporation, Devor Publications, Inc., Mineola, New York (2004).
46. Ringuest, J.L. "Lp-metric sensitivity analysis for single and multi-attribute decision analysis", *European Journal of Operational Research*, **98**(3), pp. 563-570 (1997).
47. Cheraghalipour, A., Paydar, M.M. and Hajiaghaei-Keshteli, M. "Applying a hybrid BWM-VIKOR approach to supplier selection: A case study in the Iranian agricultural implements industry", *International Journal of Applied Decision Sciences*, **11**(3), pp. 274-301 (2018).
48. Abdi, A., Abdi, A., Akbarpour, N., Amiri, A.S. and Hajiaghaei-Keshteli, M. "Innovative approaches to design and address green supply chain network with simultaneous pick-up and split delivery", *Journal of Cleaner Production*, **250**, p. 119437 (2020).
49. Abdi, A., Abdi, A., Fathollahi-Fard, A.M. and Hajiaghaei-Keshteli, M. "A set of calibrated metaheuristics to address a closed-loop supply chain network design problem under uncertainty", *International Journal of Systems Science: Operations & Logistics*, **8**(1), pp. 23-40 (2021).
50. Amiri, S.A.H.S., Zahedi, A., Kazemi, M., Soroor, J. and Hajiaghaei-Keshteli, M. "Determination of the optimal sales level of perishable goods in a two-echelon supply chain network", *Computers & Industrial Engineering*, **139**, p. 106156 (2020).
51. Michalewicz, Z., Vignaux, G.A. and Hobbs, M. "A nonstandard genetic algorithm for the nonlinear transportation problem", *ORSA Journal on Computing*, **3**(4), pp. 307-316 (1991).
52. Prüfer, H. "Neuer beweis eines satzes über permutationen. *Arch. Math. Phys*, **27**(1918), pp. 742-744 (1918).
53. Gen, M., Altiparmak, F. and Lin, L. "A genetic algorithm for two-stage transportation problem using priority-based encoding", *OR Spectrum*, **28**(3), pp. 337-354 (2006).
54. Hajiaghaei-Keshteli, M. and Aminnayeri, M. "Solving the integrated scheduling of production and rail transportation problem by Keshtel algorithm", *Applied Soft Computing*, **25**, pp. 184-203 (2014).
55. Mosallanezhad, B., Chouhan, V.K., Paydar, M.M. and Hajiaghaei-Keshteli, M. "Disaster relief supply chain design for personal protection equipment during the COVID-19 pandemic", *Applied Soft Computing*, **112**, p. 107809 (2021).
56. Kirkpatrick, S., Gelatt, C.D. and Vecchi, M.P. "Optimization by simulated annealing", *Science*, **220**(4598), pp. 671-680 (1983).
57. Akbarpour, N., Hajiaghaei-Keshteli, M. and Tavakkoli-Moghaddam, R. "New approaches in meta-heuristics to schedule purposeful inspections of workshops in manufacturing supply chains", *International Journal of Engineering*, **33**(5), pp. 833-840 (2020).
58. Hajipour, V., Mehdizadeh, E. and Tavakkoli-Moghaddam, R. "A novel Pareto-based multi-objective vibration damping optimization algorithm to solve multi-objective optimization problems", *Scientia Iranica. Transaction E, Industrial Engineering*, **21**(6), p. 2368 (2014).
59. Al Jadaan, O., Rajamani, L. and Rao, C.R. "Non-dominated ranked genetic algorithm for solving multiobjective optimization problems: NPGA", *Journal of Theoretical and Applied Information Technology*, **4**(1), pp. 60-68 (2008).
60. Deb, K., Pratap, A., Agarwal, S. and Meyarivan, T.A.M.T. "A fast and elitist multiobjective genetic algorithm: NSGA-II", *IEEE Transactions on Evolutionary Computation*, **6**(2), pp. 182-197 (2002).
61. Babashahi, M., Shahanaghi, K., Gholamian, M.R. and Yavari, A. "A bi-objective hierarchical hub location model with facility failure", *Scientia Iranica*, **27**(4), pp. 2009-2020 (2020).




62. Fathollahi-Fard, A.M., Hajiaghaei-Keshteli, M., Tavakkoli-Moghaddam, R. and Smith, N.R. "Bi-level programming for home health care supply chain considering outsourcing", *Journal of Industrial Information Integration*, Art. No. 100246 (2021).
63. Sahebjamnia, N., Goodarzian, F. and Hajiaghaei-Keshteli, M. "Optimization of multi-period three-echelon citrus supply chain problem", *Journal of Optimization in Industrial Engineering*, **13**(1), pp. 39-53 (2020).
64. Bahadori-Chinibelagh, S., Fathollahi-Fard, A.M. and Hajiaghaei-Keshteli, M. "Two constructive algorithms to address a multi-depot home healthcare routing problem", *IETE Journal of Research*, Article in Press, pp. 1-7 (2019).
65. Taguchi, G. "*Introduction to quality engineering: designing quality into products and processes*", Asian Productivity Organization, Tokyo (1986).
66. Cheraghalipour, A., Paydar, M.M. and Hajiaghaei-Keshteli, M. "Designing and solving a bi-level model for rice supply chain using the evolutionary algorithms", *Computers and Electronics in Agriculture*, **162**, pp. 651-668 (2019).
67. Cheraghalipour, A., Paydar, M.M. and Hajiaghaei-Keshteli, M. "An integrated approach for collection center selection in reverse logistics", *International Journal of Engineering*, **30**(7), pp. 1005-1016 (2017).
68. Gholian-Jouybari, F., Afshari, A.J. and Paydar, M.M. "Utilizing new approaches to address the fuzzy fixed charge transportation problem", *Journal of Industrial and Production Engineering*, **35**(3), pp. 148-159 (2018).
69. Gholian Jouybari, F., Afshari, A.J. and Paydar, M.M. "Electromagnetism-like algorithms for the fuzzy fixed charge transportation problem", *Journal of Industrial Engineering and Management Studies*, **3**(1), pp. 39-60 (2016).
70. Akbarpour, N., Salehi-Amiri, A., Hajiaghaei-Keshteli, M. and Oliva, D. "An innovative waste management system in a smart city under stochastic optimization using vehicle routing problem", *Soft Computing*, **25**(8), pp. 6707-6727 (2021).
71. Zahedi, A., Salehi-Amiri, A., Smith, N.R. and Hajiaghaei-Keshteli, M. "Utilizing IoT to design a relief supply chain network for the SARS-COV-2 pandemic", *Applied Soft Computing*, **104**, p. 107210 (2021).
72. Zahedi, A., Salehi-Amiri, A., Hajiaghaei-Keshteli, M. and Diabat, A. "Designing a closed-loop supply chain network considering multi-task sales agencies and multi-mode transportation", *Soft Computing*, **25**(8), pp. 6203-6235 (2021).
73. Maghsoudlou, H., Kahag, M.R., Niaki, S.T.A. and Pourvaziri, H. "Bi-objective optimization of a three-echelon multi-server supply-chain problem in congested systems: Modeling and solution", *Computers & Industrial Engineering*, **99**, pp. 41-62 (2016).
74. Rahmati, S.H.A., Hajipour, V. and Niaki, S.T.A. "A soft-computing Pareto-based meta-heuristic algorithm for a multi-objective multi-server facility location problem", *Applied soft computing*, **13**(4), pp. 1728-1740 (2013).
75. Karimi, N., Zandieh, M. and Karamooz, H.R. "Bi-objective group scheduling in hybrid flexible flowshop: a multi-phase approach", *Expert Systems with Applications*, **37**(6), pp. 4024-4032 (2010).
76. Mousavi, R., Salehi-Amiri, A., Zahedi, A. and Hajiaghaei-Keshteli, M. "Designing a supply chain network for blood decomposition by utilizing social and environmental factor", *Computers & Industrial Engineering*, **160**, p. 107501 (2021).
77. Kazemi, M., Asef-Vaziri, A., Shojaei, T. and Amiri, S.A.H.S. "A Math-heuristic Algorithm for Concurrent Assignment and Sequence Scheduling in Multi-Shuttle Shared Location Automated Storage and Retrieval Systems", *Journal of Supply Chain and Operations Management*, **19**(1), p. 1 (2021).

## List of Figure Captions

- Figure 1.** Production of different dried fruits in 2019 and 2020 (in 1,000 metric tons)<sup>1</sup>.  
**Figure 2.** Proposed date supply chain network.  
**Figure 3.** Encode/decode strategy for Sections 1-5.  
**Figure 4.** Implemented steps of the MOKA.  
**Figure 5.** Implemented steps of multi-objective simulated annealing algorithm.  
**Figure 6.** Pseudocode of the NRGGA and NSGA-II.  
**Figure 7.** Signal-to-noise (S/N) plot for the NSGA-II.  
**Figure 8.** Signal-to-noise (S/N) plot for NRGGA.  
**Figure 9.** Signal-to-noise (S/N) plot for the MOSA algorithm.  
**Figure 10.** Signal-to-noise (S/N) plot for the MOKA.  
**Figure 11.** Interval plot of CPU time (at 95% confidence level).  
**Figure 12.** Interval plot of *MID* (at 95% confidence level).  
**Figure 13.** Pareto solution of test problem 12.



**Figure 1.** Production of different dried fruits in 2019 and 2020 (in 1,000 metric tons)<sup>2</sup>.



**Figure 2.** Proposed date supply chain network.

<sup>1</sup> [www.statista.com](http://www.statista.com)

<sup>2</sup> [www.statista.com](http://www.statista.com)

| Section 1 |      |            |      |      | Section 2 |      |          |      |      |
|-----------|------|------------|------|------|-----------|------|----------|------|------|
| <i>i</i>  |      | <i>j+m</i> |      |      | <i>j</i>  |      | <i>k</i> |      |      |
| 0.46      | 0.84 | 0.32       | 0.61 | 0.49 | 0.24      | 0.09 | 0.14     | 0.91 | 0.12 |
| 2         | 1    | 3          | 1    | 2    | 1         | 2    | 2        | 1    | 3    |

| Section 3 |      |      |            |      |
|-----------|------|------|------------|------|
| <i>k</i>  |      |      | <i>l+m</i> |      |
| 0.29      | 0.41 | 0.33 | 0.19       | 0.34 |
| 2         | 1    | 3    | 2          | 1    |

**Figure 3.** Encode/decode strategy for Sections 1-5.

1. Parameter setting, Land the  $\{N\}$  Keshtels as solutions and evaluate the fitnesses
2. Do nin-dominate sorting and calculate the corwding distance ( $CD$ )
3. Sort Keshtels, respect to the  $CD$
4. Find the Lucky Keshtels ( $LK$ )
5. Find the Best  $LK$
6. **For** each  $LK (N_i)$  **do**
  - 6.1. Swirl the Nearest Keshtel ( $NK$ ) around the  $LK$
  - 6.2. In case better food is obtained,  $NK$  is replaced by  $LK$ . For new  $NK$  go to Step 6.1
  - 6.3. Excess food available attracts  $NK$ , do swirling, else go to step 8
7. Let the  $LKs$  remain in the lake
8. The  $(N_3)$  Keshtels with worst fitnesses be replaced with the new randomly generated Keshtels
9. Move the remaining Keshtels ( $N_2$ )
10. Merge the population  $[N_1, N_2, N_3]$
11. Do non-dominate shorting and crowding distance
12. Again, sort the non-dominated Keshtels based on crowding distance
13. Select  $(N)$  better Keshtels from this merged population for the next generation
14. Do Steps 11 and 12 for the new population
15. Stop if stopping criteria meet; otherwise, go to Step 5

**Figure 4.** Implemented steps of the MOKA.

1. Parameter setting
2. Initialize and evaluation *fitness functions*  $(x, f_j(x))$
3. Best solution =  $(x, f_j(x))$
4. **For** 1 to max-iteration
  - 4.1. **Do** *mutation* operator  $(x')$
  - 4.2. Calculate the fitness function and  $(\Delta f_j)$ 
    - 4.3.1. If  $\Delta f_1 \leq 0 \ \&\& \Delta f_2 \geq 0$ 

Update the Best solution =  $(x', f_j(x'))$

Update the solution  $x=x'$
    - 4.3.2. Else if  $\Delta f_1 \geq 0 \ \&\& \Delta f_2 \geq 0 \ \|\Delta f_1 \leq 0 \ \&\& \Delta f_2 \leq 0$ 

**Put** this solution in *Pareto* set
    - 4.3.3. Else  $\Delta f_1 \geq 0 \ \&\& \Delta f_2 \leq 0$ 

$$P_1 = \exp\left(\frac{-\Delta f_1}{T}\right), \quad P_2 = \exp\left(\frac{-\Delta f_2}{T}\right), \quad h=\text{rand}$$


If  $h < P_1 \ \&\& h < P_2$

Update the solution  $x=x'$
5. Update *temperature*  $(T=\alpha*T)$
6. **Do** non-dominate sorting in this *Pareto* set.
7. If stopping criteria are satisfied, stop, if not, go to Step 4.1.


**Figure 5.** Implemented steps of the multi-objective simulated annealing algorithm.

1. Initialize population
2. Generate random population
3. Evaluate objective values
4. **For** each parent and population **do**
  - 4.1. Assign rank based on Pareto
  - 4.2. Generate sets on Non-dominated solutions
  - 4.3. Determine Crowding distance
  - 4.4. Loop by adding solutions to the next generation
5. Determine population front
8. **For** each determined front **do**
  - 8.1. Perform binary tournament solution (NRGA) / Roulette wheel selection (NSGA-II)
9. Generate new population with crossover and mutation

**Figure 6.** Pseudo code of the NRGA and NSGA-II.



**Figure 7.** Signal-to-noise (S/N) plot for the NSGA-II.



**Figure 8.** Signal-to-noise (S/N) plot for the NRGA.




Figure 9. Signal-to-noise (S/N) plot for the MOSA algorithm.




Figure 10. Signal-to-noise (S/N) plot for the MOKA.




Figure 11. Interval plot of the CPU time (at 95% confidence level).




Figure 12. Interval plot of the MID (at 95% confidence level).




Figure 13. Pareto solution of test problem 12.

### List of Table Captions

- Table 1.** Notations of the presented model.
- Table 2.** Problem classification.
- Table 3.** Values of parameters.
- Table 4.** Proposed meta-heuristic algorithm in terms of their levels and factors ( $x=i+j+k+l+m$ ).
- Table 5.** Algorithm's tuned parameters.
- Table 6.** Algorithm evaluation in each considered metric ( $\times 10^6$ ).
- Table 7.** Pareto solutions based on weights.
- Table 8.** Behavior of the model with a change in demand rate.
- Table 9.** Model behavior when changing transportation parameters.
- Table 10.** Behavior of the model with change in emission rate.

**Table 1.** Notations of the presented model.

| <b>Indices:</b>            |  |
|----------------------------|--|
| $i$                        | Index of date farmland ( $i = 1, 2, \dots, I$ )  |
| $j$                        | Index of collection and distribution center ( $j = 1, 2, \dots, J$ )                               |
| $k$                        | Index of date factory ( $k = 1, 2, \dots, K$ )   |
| $l$                        | Index of customer ( $l = 1, 2, \dots, L$ )   |
| $m$                        | Index of by-product factory ( $m = 1, 2, \dots, M$ )   |
| <b>Parameters:</b>         |  |
| $f_i$                      | Fixed costs of opening date farmland $i$   |
| $f_k$                      | Fixed costs of opening date factory $k$  |
| $f_m$                      | Fixed costs of opening to by-product factory $m$   |
| $C_{ij}$                   | Processing and transportation cost from farmland $i$ to collection and distribution center $j$     |
| $C_{jk}$                   | Processing and transportation cost from collection and distribution center $j$ to date factory $k$ |
| $C_{kl}$                   | Processing and transportation cost from date factory $k$ to customers $l$                          |
| $C_{im}$                   | Processing and transportation cost from farmland $i$ to by-factory $m$                             |
| $C_{km}$                   | Processing and transportation cost from date factory $k$ to by-factory $m$                         |
| $D_l$                      | Demand of date by customer $l$   |
| $\xi_i$                    | Production capacity of farmland $i$  |
| $\xi_j$                    | Capacity of collection and distribution center $j$   |
| $\xi_k$                    | Production capacity of date factory $k$  |
| $\xi_m$                    | Production capacity of by-product factory $m$  |
| $v_i$                      | Waste rate by date farmland $i$  |
| $\rho_k$                   | Waste rate by date factory $k$   |
| $EM$                       | Total amount of $CO_2$ emission  |
| <b>Decision Variables:</b> |  |
| $X_{ij}$                   | Transported quantity of product from farmland $i$ to collection and distribution center $j$        |
| $G_{jk}$                   | Transported quantity of product from collection and distribution center $j$ to date factory $k$    |
| $S_{kl}$                   | Transported quantity of product from date factory $k$ to customer $l$                              |
| $E_{km}$                   | Transported quantity of product from date factory $k$ to by-product factory $m$                    |
| $R_{im}$                   | Transported quantity of waste date from date farmland $i$ to by-product factory $m$                |
| $U_i$                      | 1 if date farmland $i$ is opened during location; 0, otherwise                                     |
| $W_k$                      | 1 if date factory $k$ is opened at location; 0, otherwise  |
| $B_m$                      | 1 if cosmetic factory $m$ is opened at location; 0, otherwise                                      |

**Table 2.** Problem classification.

| Classification | Instance | Problem size ( $i, j, k, l, m$ ) |
|----------------|----------|----------------------------------|
| Small          | $SP_1$   | (6, 6, 6, 6, 6)                  |
|                | $SP_2$   | (7, 8, 8, 8, 6, 7)               |
|                | $SP_3$   | (15, 12, 12, 12, 8)              |
| Medium         | $MP_4$   | (25, 25, 25, 25, 12)             |
|                | $MP_5$   | (35, 35, 35, 35, 35)             |
|                | $MP_6$   | (60, 60, 45, 45, 45, 45)         |
|                | $MP_7$   | (70, 65, 50, 50, 50, 50)         |

| Classification | Instance  | Problem size ( $i, j, k, l, m$ ) |
|----------------|-----------|----------------------------------|
| Large          | $LP_8$    | (120, 100, 100, 100, 80)         |
|                | $LP_9$    | (150, 150, 150, 150, 80)         |
|                | $LP_{10}$ | (200, 200, 200, 200, 100)        |

**Table 3.** Values of parameters.

| Parameters | Value                      | Parameters | Value                      |
|------------|----------------------------|------------|----------------------------|
| $f_i$      | $Uniform\sim[14000,24000]$ | $D_l$      | $Uniform\sim[15000,20000]$ |
| $f_k$      | $Uniform\sim[22500,37000]$ | $\xi_i$    | $Uniform\sim[5500,7900]$   |
| $f_m$      | $Uniform\sim[15000,18300]$ | $\xi_j$    | $Uniform\sim[4150,6100]$   |
| $C_{ij}$   | $Uniform\sim[7300,8500]$   | $\xi_k$    | $Uniform\sim[6120,7200]$   |
| $C_{jk}$   | $Uniform\sim[4600,5200]$   | $\xi_m$    | $Uniform\sim[1590,4190]$   |
| $C_{kl}$   | $Uniform\sim[6940,7200]$   | $v_i$      | $Uniform\sim[0.46,0.79]$   |
| $C_{im}$   | $Uniform\sim[3000,5000]$   | $\rho_k$   | $Uniform\sim[0.26,0.49]$   |
| $C_{km}$   | $Uniform\sim[3200,4800]$   | $EM$       | $Uniform\sim[0.11,0.91]$   |

**Table 4.** Proposed meta-heuristic algorithm in terms of their levels and factors ( $x=i+j+k+l+m$ ).

| Algorithms | Factor             | Level 1 | Level 2 | Level 3 |
|------------|--------------------|---------|---------|---------|
| NSGA-II    | A: $P_c$           | 0.62    | 0.71    | 0.84    |
|            | B: $P_m$           | 0.16    | 0.18    | 0.21    |
|            | C: $N-pop$         | 65      | 125     | 185     |
|            | D: $Max-iteration$ | 2x      | 3x      | 4x      |
| NRGA       | A: $P_c$           | 0.62    | 0.71    | 0.84    |
|            | B: $P_m$           | 0.16    | 0.18    | 0.21    |
|            | C: $N-pop$         | 65      | 125     | 185     |
|            | D: $Max-iteration$ | 2x      | 3x      | 4x      |
| MOKA       | A: $M_1$           | 16%     | 14%     | 19%     |
|            | B: $M_2$           | 25%     | 15%     | 35%     |
|            | C: $S_{max}$       | 0.22    | 0.26    | 0.31    |
|            | D: $N-Keshtel$     | 180     | 220     | 240     |
|            | E: $Max-iteration$ | 2x      | 3x      | 4x      |
| MOSA       | A: $T_0$           | 1200    | 1400    | 1500    |
|            | B: $\alpha$        | 0.93    | 0.94    | 0.95    |
|            | C: $Max-iteration$ | 2x      | 3x      | 4x      |

**Table 5.** Algorithm's tuned parameters.

| Algorithm | Parameters  |
|-----------|---|
| NSGA-II   | $P_c=0.71; P_m=0.16; N-pop=65; Max-iteration=3x$                  |
| NRGA      | $P_c=0.62; P_m=0.16; N-pop=125; Max-iteration=4x$                 |
| MOSA      | $T_0=1400; \alpha=0.94; Max-iteration=2x$                         |
| MOKA      | $M_1=19%; M_2=15%; S_{max}=0.26; N-Keshtel=180; Max-iteration=4x$ |

**Table 6.** Algorithm evaluation in each considered metric ( $\times 10^6$ ).

| Problem | MID      |          |          |          | CPU Time |          |          |          |
|---------|----------|----------|----------|----------|----------|----------|----------|----------|
|         | NSGA-II  | NRGA     | MOKA     | MOSA     | NSGA-II  | NRGA     | MOKA     | MOSA     |
| 1       | 1.624768 | 2.578007 | 1.536059 | 4.25988  | 68.47097 | 75.67316 | 116.7185 | 20.12469 |
| 2       | 1.219475 | 1.283882 | 1.280612 | 2.535287 | 149.7642 | 167.6113 | 281.0178 | 31.64245 |
| 3       | 2.304143 | 2.208677 | 3.183059 | 2.329862 | 258.7157 | 285.9377 | 526.7324 | 33.56238 |



|    |          |          |          |          |          |          |          |          |
|----|----------|----------|----------|----------|----------|----------|----------|----------|
| 4  | 3.936104 | 2.30447  | 2.53398  | 5.991338 | 391.9419 | 444.071  | 811.2392 | 36.31603 |
| 5  | 4.027755 | 2.846531 | 4.020017 | 3.503348 | 966.2851 | 1082.003 | 2193.278 | 46.1929  |
| 6  | 3.473815 | 3.056752 | 3.62693  | 5.484041 | 1281.524 | 1387.456 | 2446.077 | 50.59081 |
| 7  | 5.464861 | 5.928349 | 4.627248 | 5.252679 | 1494.515 | 1670.263 | 2864.669 | 55.64986 |
| 8  | 6.403497 | 6.169192 | 5.824165 | 5.42225  | 2511.428 | 2821.97  | 6080.222 | 87.96949 |
| 9  | 5.278725 | 4.446016 | 7.323934 | 5.601085 | 6013.592 | 5458.181 | 11124.6  | 117.0055 |
| 10 | 4.319274 | 4.040941 | 11.21143 | 6.368079 | 6622.533 | 6091.259 | 13198.63 | 127.1979 |

**Table 7.** Pareto solutions based on weights.

| Weights        | 0.1       | 0.2       | 0.3       | 0.4       | 0.5       | 0.6       | 0.7       | 0.8       | 0.9       | 1         |
|----------------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|
| Total Cost     | 290618.59 | 304753.64 | 320647.13 | 316390.67 | 320052.75 | 318216.38 | 329500.07 | 320394.99 | 316177.14 | 318504.07 |
| Total emission | 230.84    | 234.22    | 235.89    | 237.75    | 237.90    | 239.62    | 241.35    | 239.86    | 240.06    | 232.17    |
| Total Cost     | 293667.80 | 306471.41 | 316503.66 | 316325.35 | 323808.47 | 317307.26 | 329059.95 | 318097.20 | 317380.28 | 318979.06 |
| Total emission | 232.45    | 234.23    | 236.04    | 237.76    | 237.92    | 239.45    | 241.16    | 234.99    | 238.42    | 232.17    |
| Total Cost     | 296277.81 | 315257.34 | 317618.36 | 317745.92 | 327648.99 | 317838.06 | 316916.04 | 323759.57 | 318803.01 | 325250.24 |
| Total emission | 232.51    | 234.27    | 237.54    | 239.28    | 237.95    | 239.55    | 241.37    | 235.20    | 241.64    | 232.17    |
| Total Cost     | 301692.27 | 316466.93 | 322083.67 | 318036.74 | 317826.76 | 322294.48 | 317185.26 | 324957.53 | 321074.35 | 325427.14 |
| Total emission | 232.54    | 234.28    | 237.59    | 239.32    | 239.38    | 241.15    | 242.92    | 236.71    | 241.67    | 232.17    |

**Table 8.** Behavior of the model with a change in demand rate.

|                     | $D_t$  |        |        |
|---------------------|--------|--------|--------|
|                     | 40 % ↑ | 0 %    | 40 % ↓ |
| Opening Cost        | 0.00%  | -      | 1.28%  |
| Processing Cost     | 0.01%  | -      | -1.10% |
| Transportation Cost | 1.52%  | -      | 3.11%  |
| Objective function  | NRGA   | 3.122% | -2.43% |
|                     | MOSA   | 3.768% | -2.55% |
|                     | MOKA   | 2.131% | -2.25% |

|  |         |        |   |        |
|--|---------|--------|---|--------|
|  | NSGA-II | 1.491% | - | -2.12% |
|--|---------|--------|---|--------|

**Table 9.** Model behavior when changing transportation parameters.

|                    |         | <i>(Total transportation cost)</i> |        |     |        |         |
|--------------------|---------|------------------------------------|--------|-----|--------|---------|
|                    |         | 40 % ↑                             | 20 % ↑ | 0 % | 20 % ↓ | 40 % ↓  |
| Opening cost       |         | 36.13%                             | 7.92%  | -   | 0.00%  | -20.20% |
| Processing cost    |         | 1.83%                              | 3.04%  | -   | -4.45% | -1.07%  |
| Objective function | NRGA    | 9.03%                              | 9.03%  | -   | -7.32% | -15.16% |
|                    | MOSA    | 9.17%                              | 9.17%  | -   | -5.47% | -13.72% |
|                    | MOKA    | 9.11%                              | 9.11%  | -   | -7.07% | -14.54% |
|                    | NSGA-II | 7.93%                              | 7.93%  | -   | -6.35% | -13.39% |

**Table 10.** Behavior of the model with change in the emission rate.

|                     |         | <i>EM(Emission rate)</i> |        |     |         |         |
|---------------------|---------|--------------------------|--------|-----|---------|---------|
|                     |         | 40 % ↑                   | 20 % ↑ | 0 % | 20 % ↓  | 40 % ↓  |
| Opening Cost        |         | 19.15%                   | 0.00%  | -   | -5.32%  | -5.66%  |
| Operation Cost      |         | 10.30%                   | 6.17%  | -   | -6.52%  | -13.67% |
| Transportation Cost |         | 14.12%                   | 6.56%  | -   | -6.91%  | -12.99% |
| Objective function  | NRGA    | 59.24%                   | 26.73% | -   | -26.83% | -51.14% |
|                     | MOSA    | 59.88%                   | 26.04% | -   | -26.94% | -50.25% |
|                     | MOKA    | 58.56%                   | 26.37% | -   | -26.84% | -49.27% |
|                     | NSGA-II | 61.76%                   | 25.66% | -   | -26.90% | -49.07% |

#### Biography:

**Abdolreza Hamdi-Asl** is a Ph.D. student of Industrial Engineering at Islamic Azad University, Tehran, Iran. He received his B.Sc. and M.Sc. degrees in Chemical and Industrial Engineering, respectively. His research interest areas include Optimization, Multi-objective evolutionary algorithm, Supply chain network design, and Sustainable logistics. He has published several papers in journals and conferences. Also, he has more than twenty years of managerial experience in the oil and petroleum industries.

**Hossein Amoozad Khalili** is an Assistant Professor in the Department of Industrial Engineering at the Islamic Azad University. He received his B.Sc. degree in Industrial Engineering from Iran University of Science and Technology and his M.Sc. and Ph.D. degrees in Industrial Engineering from Islamic Azad University. He supervised more than fifty master theses and also ten Ph.D. dissertations. His research interests include Transportation, Optimization, Mathematics Modeling, and Supply Chain Management. He has published several papers in refereed journals and conferences. Besides, he has been the scientific chair in several national and international conferences.

**Reza Tavakkoli-Moghaddam** is a Professor of Industrial Engineering at the College of Engineering, University of Tehran, Iran. He obtained his Ph.D., M.Sc., and B.Sc. degrees in Industrial Engineering from the Swinburne University of Technology in Melbourne (1998), the University of Melbourne in Melbourne (1994), and the Iran University of Science and Technology in Tehran (1989), respectively. He serves as the Editor-in-Chief of the Journal of Industrial Engineering published by the University of Tehran and as the Editorial Board member of nine reputable academic journals. He is the recipient of the 2009 and 2011 Distinguished Researcher Awards and the 2010 and 2014 Distinguished Applied Research Awards at the University of Tehran, Iran. He was selected as the National Iranian Distinguished Researcher in 2008 and 2010 by the MSRT (Ministry of Science, Research, and Technology) in Iran. He has obtained an outstanding rank as the top 1% scientist and researcher in the world elite group since 2014. He also received the Order of Academic Palms Award as a distinguished educator and scholar for the insignia of Chevalier dans l'Ordre des Palmes Academiques by the Ministry of National Education of France in 2019. He has published five books, 25 book chapters, and more than 1000 journal and conference papers.

**Mostafa Hahiaghaei-Keshteli** is a Research Professor at the Department of Industrial Engineering, School of Engineering and Science, Tecnológico de Monterrey, Puebla Campus, Mexico. He has obtained his B.Sc., M.Sc., and Ph.D. degrees in Industrial Engineering. He is the founder and head of the research department at the Center of Sustainable and Smart Logistics (CSSL) and a member of the Optimization and Data Science research center. His main research areas are Sustainable and Smart Logistics, Supply Chain Integration and Optimization, Industry 4.0 and 5.0, and Combinatorial Optimization. In this research area, he has first designed and developed some food

and agricultural supply chains (e.g., Citrus, Rice, Sugarcane, Avocado, Walnut, and fish). He is also the inventor of some famous and capable meta-heuristic algorithms in optimizations, such as Keshtel Algorithm (2012), Red Deer Algorithm (2016), Social Engineering Optimizer (2018), and Tree Growth Algorithm (2018).