

# A virtual blind spot identification system (VIBSIM) for construction projects

S. Kivrak\* and F. Rostami Kia

*Department of Civil Engineering, Anadolu University, Iki Eylul Campus, 26555*

*Eskisehir, Turkey*

**Abstract.** The construction industry is recognized as one of the most hazardous industries. Visibility-related accidents are the cause of a significant portion of the total fatalities within the construction industry. Limited visibility due to construction equipment blind spots and a lack of visibility in construction areas such as slab openings are among the main causes of these fatalities. This study introduces the Virtual Blind Spot Identification System (VIBSIM), which was designed to identify and examine blind spots in construction equipment and construction sites. The VIBSIM consists of a three-dimensional point cloud model that uses 3ds Max software in conjunction with a V-Ray rendering motor. A real case is used to validate the applicability of the proposed system. The results indicate that the system can significantly improve safety applications for construction projects. Moreover, the system can aid construction managers in making decisions regarding the better management of such safety applications for construction projects.

**KEYWORDS:** Blind spot, Construction accidents, Point cloud, Safety, VIBSIM, Visibility

---

\*. *Corresponding author. Tel.: +90 222 3213550; Fax: +90 222 3239501*  
*E-mail addresses: serkankivrak@anadolu.edu.tr (S. Kivrak); saytec@gmail.com (F.Rostami Kia)*

25 **1. Introduction**

26

27 Although safety performance in the construction industry has improved in recent  
28 years, the accident and fatality rates in this industry are still among the highest  
29 across all sectors [1]. Indeed, the United States Bureau of Labor Statistics (BLS)  
30 reported that the construction sector had the largest number of fatal workplace  
31 injuries (805 out of 4,628 total fatalities) in 2012 [2]. Aside from causing human  
32 tragedy and economic loss, such accidents also significantly affect the  
33 productivity and reputation of the construction industry [3,4]. Therefore,  
34 minimizing accidents is a major issue that the industry must solve [5].

35

36 The BLS report stated that the main causes of fatalities on construction sites are  
37 falls (34.6%), being struck by objects (9.8%), electrocution (8.1%), and being  
38 caught in-between equipment or objects (1.6%) [2]. Furthermore, according to the  
39 Occupational Safety and Health Administration (OSHA), approximately 360  
40 workers in the United States died due to backover incidents between 2005 and  
41 2010 [6]. These statistics show that equipment-related fatalities comprise a  
42 significant portion of the total fatalities within the construction industry. One of  
43 the main causes of equipment-related fatalities is limited visibility due to blind  
44 spots [7,8], which are defined as areas that are not visible to the equipment  
45 operator [9]. Blind spots create problems for equipment operators by restricting  
46 their line of sight [10]. According to the study by Hinze and Teizer [11],  
47 visibility-related construction accidents accounted for nearly 5% of all  
48 construction industry fatalities from 1990 to 2007 in the United States. Some

49 fatalities caused by falling from a height can also be attributed to visibility issues  
50 in areas of a construction site such as stairs as well as slab and wall openings.  
51 Thus, identifying blind spots is critical to the prevention of visibility-related  
52 accidents.

53

54 Information technologies play a vital role in improving the construction industry's  
55 safety performance [12-14]. Although many studies have shown that the  
56 construction industry is reluctant to apply new technologies [15], the sector has  
57 become more aware of the need for advanced technology over the past few years  
58 [16]. Based on the above, this research study aims to reduce the likelihood of  
59 visibility-related accidents by using a blind spot identification system.

60

61 In recent years, various methods and technology applications have been  
62 developed to identify blind spots on construction equipment and thereby to reduce  
63 the number of visibility-related accidents that occur on construction sites [17-21].  
64 Previous studies on blind spot identification have generally analyzed the  
65 machinery, equipment, site conditions, and operators' physical properties, and  
66 such studies have developed blind spot area diagrams as well as proposing various  
67 methods and technologies aimed at accident prevention. For instance, Hefner [22]  
68 published a library of blind spot diagrams for a total of 38 different vehicles used  
69 in the construction industry. Similarly, the National Institute for Occupational  
70 Safety and Health (NIOSH) has developed blind spot diagrams for 43 pieces of  
71 construction equipment based on manual methods and the ISO standards 5006 and  
72 14401-1 [23]. Teizer [24] introduced a three-dimensional (3D) imaging system

73 that is useful for safety applications and night operations, where static and  
74 dynamic objects can scarcely be recognized by existing intensity- or color-based  
75 sensing systems. Teizer et al. [10] presented an automated blind spot detection  
76 tool that determines equipment blind spots rapidly and in 3D by analyzing point  
77 cloud data from a laser scan inside the cab. Another study by Teizer et al. [25]  
78 aimed to improve safety in construction equipment operations by using  
79 autonomous, wireless, proactive, real-time warning and alert devices when two or  
80 more construction resources are in close proximity. Ray and Teizer [9] proposed a  
81 new approach to computing blind spots, which involved the use of equipment  
82 point cloud data. Their method enables the performance of various analyses, such  
83 as volumetric blind spots, blind spot mapping, 12 m circumference visibility,  
84 rectangular 1 m boundary visibility, and worker visibility [9]. Marks et al. [26]  
85 also used laser scanning data to measure blind spots, and they demonstrated how  
86 the design of construction equipment impacts operator visibility. A more recent  
87 study conducted by Bostelman et al. [27] provided an explanation of visibility  
88 measurement experiments, as well as the associated results, language suggestions  
89 for standards organizations, and a prototype design for automatically measuring  
90 the visibility of forklifts.

91

92 Some researchers have focused on the particular blind spot problems of tower  
93 cranes [28-31]. For instance, Lee et al. [32] introduced a tower crane navigation  
94 system that provides 3D information about the building, surroundings, and  
95 position of the lifted object in real-time using various sensors and a building  
96 information model. A similar system was presented by Lee et al. [33], who used a

97 radio-frequency identification tag system developed for the T-type tower crane.  
98 Shapira et al. [34] developed a wireless video camera for tower cranes that offers  
99 a solution to the problem of blind lifts. Further, Fang and Teizer [35] presented a  
100 virtual training approach intended to enhance the collaboration between crane  
101 operators and signal people in blind lifting operations. Cheng and Teizer [36]  
102 introduced a framework to explain the method of streaming data from real-time  
103 positioning sensors to a real-time data visualization platform. In a more recent  
104 study, Cheng and Teizer [37] presented an approach aimed at increasing the  
105 situational awareness of tower crane operators by aligning an enhanced  
106 understanding of the construction site's layout with increased visibility of ground-  
107 level operations on the part of the operator.

108

109 It should be noted that all of the abovementioned methods and technologies have  
110 great potential to improve safety in relation to visibility issues in the construction  
111 industry. This study contributes to the literature by introducing a newly developed  
112 blind spot identification system known as the Virtual Blind Spot Identification  
113 System (VIBSIM). The VIBSIM facilitates blind spot identification not only for  
114 construction equipment, but also for construction areas such as stairs as well as  
115 slab and wall openings. The proposed system can be viewed as an alternative to  
116 current blind spot identification methods.

117

118

119

120

121 **2. Methods**

122

123 The VIBSIM was designed to identify and examine blind spots in construction  
124 equipment and areas of the construction site, including stairs and slab and wall  
125 openings. As part of this system, 3D models of construction sites and equipment  
126 are developed using 3ds Max 2012, one of the most powerful software systems for  
127 comprehensive modeling, as the foundation platform. Three-dimensional  
128 construction equipment models are generally provided by manufacturers.  
129 However, in the absence of construction project models, a 3D model of the project  
130 should be modeled using the available drawings. The analysis methods used in the  
131 VIBSIM are all based on real-life rules and factors. The 3D models that form the  
132 basis of the project must be as close to reality as possible. Thus, during the  
133 transfer to 3ds Max phase of the project, several important points should be  
134 considered:

- 135 • The construction project and equipment scales must be the same as the  
136 actual measurements of the real model.
- 137 • All prepared 3D models should have the same details and parts as the real  
138 model.
- 139 • Any modeling errors in the imported models have to be reconsidered.
- 140 • Mirror and glass mesh both have to be modeled as is.
- 141 • Unneeded mesh should be deleted.

142

143 The 3ds Max software was used in the preparation of a simulation space for the  
144 blind spot analysis, while V-Ray, one of the most powerful 3ds Max rendering

145 engines, was used in the blind spot analysis phase. The use of V-Ray's computing  
146 power provided the most realistic blind spot simulation possible. However, in  
147 order to achieve the desired result, some changes were made to V-Ray's results  
148 assembly method. Normally, V-Ray provides two-dimensional images, so  
149 changes had to be made to provide 3D analyzable results. Virtually all modern  
150 global illumination renderers are based on the rendering equation introduced by  
151 Kajiya [38], who also proposed a method for computing an image based on the  
152 rendering equation using a Monte Carlo method called path tracing. Different  
153 formulations of the rendering equation are possible, but the one proposed by  
154 Kajiya [38], which is also used in this study, is as follows:

155

$$156 \quad L(x, x_1) = g(x, x_1) [e(x, x_1) + \int_S r(x, x_1, x_2) L(x_1, x_2) dx_2]$$

157 where

- 158 •  $L(x, x_1)$  is related to the light passing from point  $x_1$  to point  $x$ ;
- 159 •  $g(x, x_1)$  is a geometry (or visibility) term;
- 160 •  $e(x, x_1)$  is the intensity of light emitted from point  $x_1$  towards point  $x$ ;
- 161 •  $r(x, x_1, x_2)$  is related to the light scattered from point  $x_2$  to point  $x$  through  
162 point  $x_1$ ; and
- 163 •  $S$  is the union of all surfaces in the scene, while  $x$ ,  $x_1$ , and  $x_2$  are points  
164 from  $S$ .

165

166 The above equation states that the transport intensity of light from one surface  
167 point to another is simply the sum of the emitted light and the total light intensity  
168 that is scattered toward  $x$  from all other surface points [38]. The V-Ray irradiance

169 map calculation method was used to obtain 3D point cloud models. Irradiance is a  
170 function defined for any point in the 3D space, and it represents the light arriving  
171 at this point from all possible directions. In V-Ray, the term “irradiance map”  
172 refers to a method of efficiently computing the diffused surface irradiance for  
173 objects in the scene. The irradiance map is, in fact, a collection of points in 3D  
174 space (i.e., a point cloud) along with the computed indirect illumination at those  
175 points [39]. This point cloud is almost identical to laser scanner results.  
176 Furthermore, all of these points are fully computer-based, and they are prepared  
177 without the need for a physical model and environment.

178

179 Various types of equipment are used on construction sites, each of which has its  
180 own specific physical and visual parameters. Similarly, construction sites differ  
181 from each other and all have their own specific properties. While 3D models of  
182 construction equipment can be created and used as modular types for different  
183 projects, it is almost impossible to create a modular type for construction sites.  
184 Therefore, each construction site has to be modelled separately in order to identify  
185 the blind spots. The same is partly true for construction workers. When gathering  
186 a worker point cloud, their heights and visual distances have to be considered.  
187 Further, as each worker has a distinct height and visual distance, it is inevitable  
188 that individual measurements need to be made. The VIBSIM applications for  
189 construction equipment, construction sites, and construction workers are  
190 illustrated in the following sections.

191

192



193 **3. Case Study**

194

195 The test applications of the proposed system were conducted on a building  
196 construction site in Ankara, Turkey. The main purpose of the case study was to  
197 validate the system in a real construction project and examine its feasibility in  
198 identifying blind spots.

199

200 ***3.1. Application of the VIBSIM in construction equipment***

201 Two pieces of construction equipment, namely a hydraulic excavator and a dump  
202 truck, were selected for blind spot analysis at the construction site. The 3D models  
203 necessary for the VIBSIM analysis were prepared using 3ds Max.

204

205 Based on ISO 5006 specifications [40], the test domain radius was set to 12 m. In  
206 the VIBSIM, the central angle view of a person is considered to be 40–60 degrees.  
207 Therefore, the person sees an image close to the camera image with a focal length  
208 of 50 mm [41]. In this model, two cameras with a range of 65 mm were used to  
209 simulate the equipment operator's vision. Based on ISO 5006 standards [40], the  
210 cameras were located 68 cm above the operator's seat in order to obtain an  
211 approximate model of the operator's view (Fig. 1).

212

213 An average person is capable of rotating his head up to 80–95 degrees without  
214 twisting his body. Twisting the body can increase oscillation to 160–175 degrees  
215 [42]. Based on these numbers, directions and angles were specified in the  
216 VIBSIM model as shown in Figure 2. In addition to these angles, views from the

217 mirror and closed-circuit television camera were added to analyze the views and  
218 directions.

219

220 After placing the cameras on the equipment in the specified locations, each  
221 camera was analyzed to create point clouds of the models using V-Ray irradiance  
222 maps derived from indirect illumination. In order to obtain better and more  
223 unified results, the irradiance maps of the two pieces of equipment were merged  
224 together in the irradiance map settings.

225

226 Figures 3 and 4 show the 3D point cloud results of the hydraulic excavator model  
227 used in the VIBSIM. The shaded areas illustrate the blind spot areas of the  
228 equipment, while the dark areas represent the visible points. The cropped  
229 hemisphere is the maximum range of the operator's effective sight.

230

231 The blind spots prepared in the 3D model space make it possible to examine the  
232 analysis results from various points of view. Moreover, in order to gain more  
233 detailed blind spot information, it is also possible to calculate the percentage of  
234 blind spots by dividing the blind spot volume by the total volume (i.e., blind spots  
235 plus visible spaces) using 3ds Max. A similar method was used in the study  
236 conducted by Teizer et al. [10]. In their study, to calculate the percentage of blind  
237 spots in the 3D grid, they counted the number of cubes that are labeled as part of  
238 the "blind" spots and the number of cubes that are labeled "visible", and finally  
239 they obtained the percentage of blind spots by dividing the sum of the number of  
240 blind cubes by the sum of the number of blind and visible cubes.

241

242 A 3D model analysis can be performed for each piece of construction equipment  
243 using the same method. In addition to creating these 3D models, it is also possible  
244 to determine the distances and coordinates at which both equipment and workers  
245 enter the risk area. For example, the point where a worker who is 175 cm tall  
246 enters the danger zone can easily be determined. In this regard, 3D point clouds  
247 that have been obtained in advance can be used to determine the locations of  
248 workers of any height in different areas of the construction site. Figures 5 and 6  
249 provide an example of workers' locations around the excavator. As shown in  
250 Figure 6, workers in equipment blind spots can be identified, and the data can then  
251 be used to take precautions and help prevent future accidents. Importantly, the  
252 models of the real site can be updated when changes are made on site. The  
253 VIBSIM allows the addition of any on-site changes to the virtual model as well as  
254 the re-building of the point cloud.

255

256 The analysis results of the VIBSIM in terms of identifying blind spots in  
257 construction equipment show similarities with those of previous studies [9-11, 21-  
258 22, 26-27]. However, the method used in the VIBSIM is totally virtual and does  
259 not require any actual laser scanning results, which is a point of distinction from  
260 the previous blind spot identification methods.

261

### 262 ***3.2. Application of the VIBSIM on construction workers***

263 The VIBSIM was also tested on construction workers. The same camera types  
264 were used for the worker analysis as were used for the equipment analysis. The

265 cameras had a 43 mm focal length and a 45° film gate with 3:2 aspect ratios. The  
266 cameras' height was 170 cm, which was considered to be the standard height of a  
267 worker. Thus, an approximate perspective view model of a worker was  
268 determined.

269

270 According to the VIBSIM's blind spot test analysis, if a worker focuses on a  
271 specific point, his field of view drops to 60–100 degrees. Thus, the constant blind  
272 spot area of a worker is approximately 260–300 degrees. Another finding is that  
273 although a worker has a fixed point of view, his field of vision changes precisely  
274 while he is moving. During movement on a construction site, a worker takes his  
275 blind spot cloud with him, and so the danger zones are constantly changing  
276 according to the movement of the worker. These blind spots are referred to as  
277 active blind spots (Fig. 7).

278

279 The left view of Figure 7 shows the minimum detection distance of a worker who  
280 is standing, which is about 4.5 m. As shown in the right view of Figure 7, an  
281 opening placed 5.35–6 m from the test's source object disappeared from view  
282 after the simulated worker moved 2 m forward. Therefore, it can be stated that a  
283 lack of dynamic blind spot identifications endangers the lives of workers. For this  
284 reason, in addition to fixed blind spots, active blind spots need to be taken into  
285 account to ensure the safety of construction workers.

286

287

288

289 **3.3. Application of the VIBSIM on construction site**

290 In addition to the visual difficulties posed by construction equipment and workers,  
291 visibility problems can also be caused by the physical conditions of construction  
292 sites. Slabs, stairs, and wall openings during the construction phase are among the  
293 major factors involved in severe accidents. In order to identify the visibility  
294 problems caused by these openings, a 3D model of our construction site was  
295 prepared. Using the workers' perspectives obtained in the previously described  
296 manner, a simulation of the real environment was obtained in the VIBSIM.  
297 Figures 8 and 9 illustrate the VIBSIM analysis results concerning workers'  
298 visibility near slab openings. Since human sight is limited to a constant amount of  
299 degrees, using the VIBSIM facilitates an analysis of any area where the worker  
300 cannot determine his distance to such openings and potential dangerous areas.

301

302 A large, unprotected opening on the roof of a building is another type of danger  
303 that can lead to serious accidents. Such accidents often occur when workers are  
304 laying or repairing a roof, and they result in the worker losing his balance and  
305 falling from a height. These falls can cause serious damage or loss of life. The  
306 worker's limited field of view, coupled with his likely focus on issues outside the  
307 workplace, is the main reason for these types of accidents. Figures 10 and 11  
308 show the VIBSIM analysis results concerning workers' visibility near roof  
309 openings.

310

311 As mentioned previously, every piece of construction equipment has its own  
312 specific blind spots. The number of blind spots increases in a construction site due

313 to obstacles such as building edges. According to the VIBSIM analysis, the  
314 number of blind spots increases as the equipment approaches the corner of a  
315 building. Figures 12 and 13 depict the blind spot model and point cloud obtained  
316 from the VIBSIM analysis. As shown in Figure 13, although the distance to a  
317 collision was very short, the drivers could still not see each other.

318

319 One of the advantages of using the VIBSIM is that it does not require real  
320 equipment for the blind spot analysis. The analysis can hence be performed in a  
321 simulated environment. Therefore, it has the potential to save time in identifying  
322 blind spots in construction areas. Further, the blind spot analysis results can easily  
323 be adapted to different pieces of equipment. As point clouds are independent (i.e.,  
324 every piece of machinery, type of equipment, labor, and construction site has its  
325 own separate blind spot point cloud), it is possible to merge previously computed  
326 blind spot point clouds with new ones. Thus, there is no need to renew the entire  
327 database for different construction sites.

328

#### 329 **4. Conclusions**

330

331 Visibility-related accidents comprise a significant portion of total accidents in the  
332 construction industry. Blind spots on construction equipment and a lack of  
333 visibility in some areas of construction sites are major factors that lead to  
334 visibility-related fatal construction accidents. In this study, the VIBSIM, a newly  
335 developed virtual blind spot identification system, was presented. The VIBSIM  
336 was designed to identify and examine the blind spots found on construction

337 equipment and construction areas such as stairs and slab and wall openings. The  
338 VIBSIM analysis method can be seen as an alternative to current blind spot  
339 identification methods. Manual methods of identifying blind spots are certainly  
340 low in cost, but their accuracy level is also low. Therefore, in order to fulfill the  
341 main purpose of the VIBSIM model, it was designed to be a computer-based  
342 model.

343

344 The VIBSIM is flexible in terms of its use. It facilitates blind spot identification  
345 not only for construction equipment, but also for construction site surroundings.  
346 This approach represents a point of differentiation from previous blind spot  
347 identification models. The validation of the proposed system was implemented at  
348 a real construction site. The VIBSIM analysis results concerning construction  
349 equipment, workers, and the construction jobsite indicated that the proposed  
350 system can significantly improve safety applications on construction projects.  
351 Another advantage of the VIBSIM is that the analysis results can be easily  
352 adapted to different types of equipment. Moreover, there is no need to renew the  
353 entire database for different construction sites. As point clouds are independent, it  
354 is possible to merge previously computed blind-spot point clouds with new ones.  
355 Using 3D point cloud models obtained with this system can assist construction  
356 managers in making decisions regarding how to better manage safety applications  
357 by identifying dangerous work areas and preventing accidents during the  
358 construction phase. Thus, the potential of the VIBSIM to reduce visibility-related  
359 accidents during construction projects offers a great benefit to the construction  
360 industry.

361

362 ***4.1. Limitations***

363 In the V-Ray irradiance map calculation method, the corresponding margin of  
364 error is  $\pm 0.1$ m, which is defined by the program itself. Based on ISO 5006  
365 standards, the experiments were carried out in an area with a 12 m radius.  
366 However, an acceptable margin of error in this experiment could extend the area  
367 of analysis to a 25 m radius.

368

369 The results of this study showed that each piece of equipment or construction site  
370 has its own blind spots that are related to its specific properties. In addition, the  
371 different sizes and visual distances of individual workers result in different blind  
372 spot perceptions. Therefore, taking into account the typical characteristics of  
373 workers and types of equipment is critical to the effectiveness of the system.  
374 Another limitation of the study is that the analyses were conducted for only one  
375 building construction site. Hence, future studies conducted for different  
376 construction sites should enhance the findings of this study.

377

378 **Acknowledgments**

379 This research was supported by the Scientific and Technological Research  
380 Council of Turkey (TUBITAK, Project No. 112M889) and the Anadolu  
381 University Scientific Research Projects Commission (Project No. 1204F064).

382

383

384



385 **References**

386

- 387 1. Wua, W., Gibb, A.G.F. and Li, Q. “Accident precursors and near misses on  
388 construction sites: an investigative tool to derive information from accident  
389 databases”, *Saf. Sci.*, **48**(7), pp. 845-858 (2010).
- 390 2. Bureau of Labor Statistics. “Census of Fatal Occupational Injuries (CFOI) -  
391 current and revised data” (2014).
- 392 3. Mohamed, S. “Empirical investigation of construction safety management  
393 activities and performance in Australia”, *Saf. Sci.*, **33**(3), pp. 129-142 (1999).
- 394 4. Marks, E.D. and Teizer, J. “Method for testing proximity detection and alert  
395 technology for safe construction equipment operation”, *Constr. Manag. Econ.*,  
396 **31**(6), pp. 636-646 (2013).
- 397 5. Zhang, S., Teizer, J., Lee, J.K., Eastman, C.M. and Venugopal, M. “Building  
398 information modeling (BIM) and safety: automatic safety checking of  
399 construction models and schedules”, *Automat. Constr.*, **29**, pp. 183-195 (2013).
- 400 6. OSHA. “OSHA seeks comments on how to prevent worker injuries and deaths  
401 from reinforcing concrete activities and vehicle backovers”, Occupational Safety  
402 & Health Administration (2012).
- 403 7. Fosbroke, D.E., “NIOSH reports! Studies on heavy equipment blind spots and  
404 internal traffic control”, *Roadway Work Zone Safety & Health Conference*,  
405 Baltimore, Maryland (2004).
- 406 8. Akula, M., Lipman, R.R., Franaszek, M., Saidi, K.S., Cheok, G.S. and Kamat,  
407 V.R. “Real-time drill monitoring and control using building information models  
408 augmented with 3D imaging data”, *Automat. Constr.*, **36**, pp. 1–15 (2013).
- 409 9. Ray, S.J. and Teizer, J. “Computing 3D blind spots of construction equipment:  
410 Implementation and evaluation of an automated measurement and visualization

- 411 method utilizing range point cloud data”, *Automat. Constr.*, **36**, pp. 95-107  
412 (2013).
- 413 10. Teizer, J., Allread, B.S. and Mantripragada, U. “Automating the blind spot  
414 measurement of construction equipment”, *Automat. Constr.*, **19**, pp. 491-501  
415 (2010).
- 416 11. Hinze, J.W. and Teizer, J. “Visibility-related fatalities related to construction  
417 equipment”, *Saf. Sci.*, **49**(5), pp. 709-718 (2011).
- 418 12. Zhou, Z., Irizarry, J. and Li, Q. “Applying advanced technology to improve  
419 safety management in the construction industry: a literature review”, *Constr.*  
420 *Manag. Econ.*, **31**(6), pp. 606-622 (2013).
- 421 13. Teizer, J., Cheng, T. and Fang, Y. “Location tracking and data visualization  
422 technology to advance construction ironworkers' education and training in safety  
423 and productivity”, *Automat. Constr.*, **35**, pp. 53-68 (2013).
- 424 14. Pradhananga, N. and Teizer, J. “Automatic spatio-temporal analysis of  
425 construction site equipment operations using GPS data”, *Automat. Constr.*, **29**,  
426 pp. 107-122 (2013).
- 427 15. Yang, L.R. “Impacts of automation technology on quality of project deliverables  
428 in the Taiwanese construction industry”, *Can. J. Civil Eng.*, **36**(3), pp. 402-414  
429 (2009).
- 430 16. Ko, C.H. 2015. “Integrating RFID, web-based technology, and artificial  
431 intelligence in engineering management”, *Scientia Iranica - Transactions A:*  
432 *Civil Engineering*, **22**(2), pp. 299-312 (2015).
- 433 17. Gai, M., Cho, Y.K. and Xu, Q. “Real-time 3D visualization of heavy  
434 construction equipment operations using LADAR”, *Proceedings of Computing in*  
435 *Civil Engineering*, pp. 889-896 (2013).

- 436 18. Choe, S., Leite, F., Seedah, D. and Caldas, C. “Evaluation of sensing technology  
437 for the prevention of backover accidents in construction work zones”, *ITcon.*, **19**,  
438 pp. 1-19 (2014).
- 439 19. Cho, Y.K. and Gai, M. “Projection-recognition-projection method for automatic  
440 object recognition and registration for dynamic heavy equipment operations”,  
441 *Journal of Computing in Civil Engineering*, **28**, Special Issue: 2012 International  
442 Conference on Computing in Civil Engineering, A4014002 (2014).
- 443 20. Wang, C. and Chob, Y.K. “Smart scanning and near real-time 3D surface  
444 modeling of dynamic construction equipment from a point cloud”, *Automat.*  
445 *Constr.*, **49**, pp. 239-249 (2015).
- 446 21. Ruff, T.M. “Monitoring blind spots - a major concern for haul trucks”, *Eng.*  
447 *Min. J.*, **202**(12), pp. 17-26 (2001).
- 448 22. Hefner, R.E. “Construction vehicle and equipment blind area diagrams”,  
449 National Institute for Occupational Safety and Health (2004).
- 450 23. NIOSH. “Highway work zone safety”, Center for Disease Control and  
451 Prevention (2011).
- 452 24. Teizer, J. “3D range imaging camera sensing for active safety in construction”,  
453 *ITcon.*, **13**, pp. 103-117 (2008).
- 454 25. Teizer, J., Allread, B.S., Fullerton, C.E. and Hinze, J. “Autonomous pro-active  
455 real-time construction worker and equipment operator proximity safety alert  
456 system”, *Automat. Constr.*, **19**, pp. 630-640 (2010).
- 457 26. Marks, E.D., Cheng, T. and Teizer, J. “Laser scanning for safe equipment design  
458 that increases operator visibility by measuring blind spots”, *ASCE J. Constr.*  
459 *Eng. Manag.*, **139**(8), pp. 1006-1014 (2013).
- 460 27. Bostelman, R., Teizer, J., Ray, S.J., Agronin, M. and Albanese, D. “Methods for  
461 improving visibility measurement standards of powered industrial vehicles”, *Saf.*  
462 *Sci.*, **62**, pp. 257-270 (2014).

- 463 28. Li, H., Chan, G. and Skitmore, M. “Integrating real time positioning systems to  
464 improve blind lifting and loading crane operations”, *Constr. Manag. Econ.*,  
465 **31**(6), pp. 596-605 (2013).
- 466 29. Wua, H., Tao, J., Li, X., Chi, X., Li, H., Hua, X., Yang, R., Wange, S. and Chen,  
467 N. “A location based service approach for collision warning systems in concrete  
468 dam construction”, *Saf. Sci.*, **51**(1), pp. 338-346 (2013).
- 469 30. Shapira, A., Simcha, M. and Goldenberg, M. “Integrative model for quantitative  
470 evaluation of safety on construction sites with tower cranes”, *ASCE J. Constr.*  
471 *Eng. Manag.*, **138**(11), pp. 1281-1293 (2012).
- 472 31. Shapira, A., Filin, S. and Wicnudel, A. 2014. “Quantitative analysis of blind  
473 tower-crane lifts using laserscanning information”, *Constr. Innov.*, **14**(3), pp.  
474 383-403 (2014).
- 475 32. Lee, G., Cho, J., Ham, S., Lee, T., Lee, G., Yun, S.H. and Yang, H.J. “A BIM-  
476 and sensor-based tower crane navigation system for blind lifts”, *Automat.*  
477 *Constr.*, **26**, pp. 1-10 (2012).
- 478 33. Lee, U.K., Kang, K.I., Kim, G.H. and Cho, H. “Improving tower crane  
479 productivity using wireless technology”, *Comput-Aided Civ. Inf.*, **21**(8), pp. 594-  
480 604 (2006).
- 481 34. Shapira, A., Rosenfeld, Y. and Mizrahi, I. “Vision system for tower cranes”,  
482 *ASCE J. Constr. Eng. Manag.*, **134**(5), pp. 320-332 (2008).
- 483 35. Fang, Y. and Teizer, J. “A multi-user virtual 3D training environment to advance  
484 collaboration among crane operator and ground personnel in blind lifts”,  
485 *Proceedings of the Computing in Civil and Building Engineering*, ASCE, pp.  
486 2071-2078 (2014).
- 487 36. Cheng, T. and Teizer, J. “Real-time resource location data collection and  
488 visualization technology for construction safety and activity monitoring  
489 applications”, *Automat. Constr.*, **34**, pp. 3–15 (2013).

490 37. Cheng, T. and Teizer, J. “Modeling tower crane operator visibility to minimize  
491 the risk of limited situational awareness”, *ASCE J. Comput. Civil Eng.*, **28**(3),  
492 04014004 (2014).

493 38. Kajiya, J.T. “The rendering equation”, *SIGGRAPH '86 Proceedings of the 13th*  
494 *annual conference on computer graphics and interactive techniques*, **20**(4), pp.  
495 143-150 (1986).

496 39. Laub, S. “VRAY for C4D\_1.0 Manual & Starter Guide” (2007).

497 40. ISO. “Earth-moving machinery—Operator’s field of view—Test method and  
498 performance criteria”, International Standard, Part 2: Evaluation method, (2011).

499 41. Maunder, M.J. de F. and Moore, P. “Lights in the sky: identifying and  
500 understanding astronomical and meteorological phenomena”, Springer  
501 Publishing, London (2007).

502 42. Barber, E.L. “Strength and range-of-motion examination skills for the clinical  
503 orthoptist”, *J. Prosthet. Orthot.* **5**, pp. 49-51 (1993).

504

505

506

507

508

509

510

511

512

513

514

515

516

517

## FIGURES

518

519 **Fig. 1.** Height of the cameras above the operator's seat.

520 **Fig. 2.** Angles and directions used in the VIBSIM.

521 **Fig. 3.** Model prepared to analyze the blind spots of the hydraulic excavator.

522 **Fig. 4.** Blind spots of the hydraulic excavator.

523 **Fig. 5.** An example of the distribution of workers around the excavator.

524 **Fig. 6.** Point cloud analysis of workers around the excavator.

525 **Fig. 7.** Active blind spots caused by movement (left view: blind spot analysis before movement; right view:  
526 blind spot analysis after 2 m forward movement).

527 **Fig. 8.** VIBSIM model of a worker near a slab opening.

528 **Fig. 9.** VIBSIM simulation results concerning a worker's visibility near a slab opening.

529 **Fig. 10.** VIBSIM model of a worker near a roof opening.

530 **Fig. 11.** VIBSIM simulation results concerning a worker's visibility near a roof opening.

531 **Fig. 12.** Blind spot model of the corner of a building.

532 **Fig. 13.** VIBSIM analysis of blind spots at the corner of a building.

533

534

535

536

537

538

539


540

541

542

543

544



545

546 **Figure 1.** Height of the cameras above the operator's seat.

547

548

549

550

551

552

553

554


555

556

557

558

559



560

561 **Figure 2.** Angles and directions used in the VIBSIM. a) North view,  $0^\circ$  angle; b) Northwest view,  
562  $45^\circ$  angle; c) Northeast view,  $-45^\circ$  angle; d) West view,  $87.5^\circ$  angle; e) East view,  $-87.5^\circ$  angle; f)  
563 Clockwise south view,  $-167.5^\circ$  angle; and g) Counter-clockwise south view,  $167.5^\circ$  angle.  
564

565

566

567


568

569

570



571



572

573 **Figure 3.** Model prepared to analyze the blind spots of the hydraulic excavator.

574

575

576

577

578

579

580

581

582

583


584

585

586

587

588



589

590 **Figure 4.** Blind spots of the hydraulic excavator.

591

592

593

594

595

596

597

598

599

600

601


602

603

604

605

606



607

608 **Figure 5.** An example of the distribution of workers around the excavator.

609

610

611

612

613

614

615

616

617

618

619

620


621

622

623

624

625



626

627 **Figure 6.** Point cloud analysis of workers around the excavator.

628

629

630

631

632

633

634

635

636

637

638

639

640


641

642

643

644

645



646

647 **Figure 7.** Active blind spots caused by movement (left view: blind spot analysis before  
648 movement; right view: blind spot analysis after 2 m forward movement).

649

650

651

652

653

654

655

656

657

658

659

660

661

662

663

664

665

666



667

668 **Figure 8.** VIBSIM model of a worker near a slab opening.

669

670

671

672

673

674

675

676

677

678

679

680


681

682

683

684

685



686

687 **Figure 9.** VIBSIM simulation results concerning a worker's visibility near a slab opening.

688

689

690

691

692

693

694

695

696

697

698


699

700

701

702

703



704

705 **Figure 10.** VIBSIM model of a worker near a roof opening.

706

707

708

709

710

711

712

713

714

715

716

717

718

719


720

721

722

723





724

725 **Figure 11.** VIBSIM simulation results concerning a worker's visibility near a roof opening.

726

727

728

729

730

731

732

733

734

735

736

737

738

739


740

741

742

743

744



745

746 **Figure 12.** Blind spot model of the corner of a building.

747

748

749

750

751

752

753

754

755

756

757

758

759

760


761

762

763

764

765



766

767 **Figure 13.** VIBSIM analysis of blind spots at the corner of a building.

768 **Biographical Details**

769 Serkan Kivrak is an Assistant Professor at the Civil Engineering Department,  
770 Eskisehir, Turkey. His research interest includes IT in construction, knowledge  
771 management, cross-cultural management and health & safety in construction.

772 Farrokh Rostami Kia obtained his Master of Science in Construction Management  
773 from Anadolu University, Turkey. His research interest includes IT in  
774 construction and health & safety in construction.

775

776